

**Code Enforcement**

285 Uptown Blvd., Cedar Hill, TX 75104
O. 972.291.5100 X 1090
F. 972.291.7250

**NOTICE OF MEETING
BOARD OF ADJUSTMENTS
Tuesday, June 5, 2018
TURK CANNADY BRIEFING ROOM-
1ST FLOOR
285 UPTOWN BLVD., BUILDING 100
1:00 p.m.**

MISSION STATEMENT: The mission of the City of Cedar Hill is to deliver the highest quality municipal services to our citizens and customers consistent with our community values.

VISION STATEMENT: We envision Cedar Hill as a premier city that retains its distinctive character, where families and businesses flourish in a safe and clean environment.

- I. Call Meeting to Order
- II. Approve the meeting minutes for Tuesday, February 13, 2018.
- III. Conduct a public hearing and consider a request by Doug Henderson with Crafton Communications to authorize the expansion of a nonconforming structure (broadcast tower/antennas) on property zoned the "SF-E" (Single-Family Residential Estate – minimum 43,560 square foot lots) District, legally described as Lot 1, Block A of the Miller Transmission Tower Addition and generally located on the south side of West Belt Line Road, west of Carrell Street with the approximate address being 1360 West Belt Line Road.
- IV. Adjourn.

I certify that the above notice of meeting was posted in accordance with the Texas Open Meetings Act on the 30th of May, 2018.

Jeanette Cosme
Jeanette Cosme

Permit Tech/Executive Assistant

MAYOR, ROB FRANKE • MAYOR PRO TEM, STEPHEN MASON • DANIEL C. HAYDIN, JR. • JAMI MCCAIN
CHRIS PARVIN • CLIFFORD R. SHAW • WALLACE SWAYZE • CITY MANAGER, GREG PORTER



Code Enforcement

285 Uptown Blvd., Cedar Hill, TX 75104
O. 972.291.5100 X 1090
F. 972.291.7250

This facility is wheelchair accessible. Handicapped parking is also available. To arrange for sign interpretative services or special accommodations, please call 972-291-5100 Ext. 1081 or (TDD) 1-800-RELAY TX (1-800-735-2989), at least 48 hours in advance of the meeting.

"PURSUANT TO SECTION 30.07, PENAL CODE (TRESPASS BY LICENSE HOLDER WITH AN OPENLY CARRIED HANDGUN), A PERSON LICENSED UNDER SUBCHAPTER H, CHAPTER 411, GOVERNMENT CODE (HANDGUN LICENSING LAW), MAY NOT ENTER THIS PROPERTY WITH A HANDGUN THAT IS CARRIED OPENLY"

"CONFORME A LA SECCIÓN 30.07, DEL CÓDIGO PENAL (ENTRADA SIN AUTORIZACIÓN POR TITULAR DE LICENCIA CON UNA PISTOLA VISIBLE), UNA PERSONA CON LICENCIA BAJO EL SUBCAPÍTULO H, CAPÍTULO 411 DEL CÓDIGO DE GOBIERNO (LEY DE LICENCIAS DE PISTOLAS), NO PUEDE ENTRAR EN ESTA PROPIEDAD CON UNA PISTOLA VISIBLE"

PREMIER STATEMENTS

Cedar Hill is Safe

Cedar Hill is Clean

Cedar Hill has Vibrant Parks and Natural Beauty

Cedar Hill has Excellent, Safe and Efficient Mobility

Cedar Hill has a Strong and Diverse Economy

Cedar Hill has Texas Schools of Choice

MAYOR, ROB FRANKE • MAYOR PRO TEM, STEPHEN MASON • DANIEL C. HAYDIN, JR. • JAMI MCCAIN
CHRIS PARVIN • CLIFFORD R. SHAW • WALLACE SWAYZE • CITY MANAGER, GREG PORTER



**Minutes
Board of Adjustments and Appeals
Meeting of Tuesday, February 13, 2018**

The Board of Adjustments of the City of Cedar Hill, Texas met on Tuesday, February 13, 2018 at 1:00 p.m. in the T.W. "Turk" Cannady-Cedar Hill Room on the 1st floor of the Government Center, City of Cedar Hill, Texas.

Present: Ray Stroh, Douglass Hibbs, Roger Welch, Michael Craig and Jerry Berry
Staff Present: Jeanette Cosme, Permit Tech, Stacey Graves, Neighborhood & Code Services Director and Gail Lux, Building Official.

I. Call the meeting to order.

Chairman Craig calls meeting to order at 1:00pm. He explained to the audience that the board must have four votes in favor for the variance to be approved.

II. Approve meeting minutes of meeting for Tuesday, January 9, 2018.

Doug Hibbs made a motion to approve the minutes from January 9, 2018 and Ray Stroh seconded the motion.

The motion was approved unanimously.

III. Review and consider a request by Judy Sudduth for an exception to the Cedar Hill Zoning Ordinance #2001-64, Section 4.1.3.E.3 Accessory Buildings to allow an accessory building without a main structure at Lot 1, Block 3, ACS 10314, Brook View unrec more commonly known as 328 Simmons Way.

Judy Sudduth is present for the meeting. She currently resides at 3706 Magnolia, Grand Prairie, TX. 75050. Judy owns the property in question and she is planning on building a home on the property but would like to build a barn there before she builds the house.

Michael Craig reads several letters of support for this request that were sent in by other property owners near hers. Gary Osborne is one of the neighbors and is present for the meeting. He just wants to see the plans and where on the property it will go on the property. He is told that it will be professionally built and that it will not be visible from the street.

Doug Hibbs asks Gail Lux, the Building Official, if the building has to meet any other requirements and Gail explains that since its under 240 sq. ft. it does not have to meet the masonry requirements. Since this property contains more than one lot, Mr. Lux wants to be sure that the structure is on the same lot which the house will be constructed because there cannot be a structure without a house.

Michael Craig explains the size of the lot and that the area is very rural and does not see a problem with it. Mr. Craig motions to approve the request contingent on the house construction to start within one year of the barn. Mr. Hibbs seconds the motion. All members vote in favor of the variance request.

IV. Review and consider a request by Tina Conner for an exception to the Cedar hill Zoning Ordinance #2001-64, Section 5.1.2.D Required Garages to allow an enclosed garage for residential living purposes without a required separate garage at Lot 5, Block 27AR, Stonewood Heights Ph. 2 Rep more commonly known as 744 Rockett Lane.

Tina Conner is present for the meeting. Tina's ex-husband converted the garage to a living area 3 years ago. She was not aware that he did this without having a permit and she recently received a notice stating that it needed to be converted back to a garage.

Mr. Craig asks if there is currently a nonfinancial hardship that could be considered for this request. At the time Ms. Conner is the only one working in the home and paying all of the expenses. Financial hardships cannot be the reason requests are granted. Mr. Craig has gone by the house and does not like how it has changed the look of the house. It stands out from the other homes in the neighborhood. There is not anyone else present to speak either for or against this request.

Ray Stroh motions to deny the request and Roger Welch seconds the motion. Members all vote to deny the request. Ms. Conner must convert the existing room back into a garage.

V. Reconsider a request by Joe Property and Construction for an exception to the Cedar Hill Zoning Ordinance #2001-64, Section 3.3.3.A Minimum Lot Area of 0.702 acres at Tract 2.6, Abstract 942, John N Gainer Survey more commonly known as 363 Lakeview Drive.

Jose Lara, the property owner, is present for the meeting. Mr. Craig explains that the lot was sized before the city changed the rules and there is no way that it could conform. The lot would be an eye sore for the area if it remains

vacant and that since this was not the fault of the owner that they should allow him to build on it.

Mr. Welch motions to approve the request and Mr. Hibbs seconds the motion. All members voted in favor of allowing Mr. Lara to build his home on the property.

VI. Review and consider a request by Joe Property and Construction for an exception to the Cedar Hill Zoning Ordinance #2001-64, Section 3.3.3.B Minimum Side Yard (interior) to allow a side yard of 10 feet at Tract 2.6, Abstract 942, John N Gainer Survey more commonly known as 363 Lakeview Drive.

Jose Lara is present for the meeting. He is asking to reduce the side yard setback so that they can build their home on it. Robbie Wiser, the property owner of the adjoining lot, is present for the meeting. He is concerned about the removal of the trees along their property. Mr. Lara explains that all of those trees will untouched and that it will not affect Mr. Wiser's property. Mr. Wiser is in favor of the home being built as described to him.

Mr. Hibbs and Mr. Craig have both been by the property and are in favor of the house being built there. They both agree that a home on a nice maintained property will look much better than what it looks like currently. Mr. Craig explains that this house will have another house to one side and that the other lot is vacant and will remain that way.

Mr. Hibbs motions to approve the request and Mr. Stroh seconds the motion. All members vote in favor of the request.

VII. Adjourn

Mr. Hibbs motions to adjourn the meeting. Mr. Stroh seconds the motion. Meeting Adjourned.

Jeanette Cosme
Jeanette Cosme/Permit Tech-Executive Assistant





PLANNING DEPARTMENT

285 Uptown Blvd.,
Cedar Hill, TX 75104
O. 972-291-5100 X1080
F. 972.291.7250

TO: Board of Adjustments and Appeals

FROM: LaShondra Stringfellow

BAA DATE: June 5, 2018

RE: Case No. 69-2018

REQUEST:

Case No. 69-2018 – An application to authorize the expansion of a nonconforming structure [broadcast tower/antennas] on property zoned the "SF-E" (Single-Family Residential Estate – minimum 43,560-square-foot lots) District, legally described as Lot 1, Block A of the Miller Transmission Tower Addition and generally located on the south side of West Belt Line Road, west of Carrell Street with the approximate address being 1360 West Belt Line Road. Applicant: Doug Henderson, Crafton Communications; Tower Owner: American Tower Corporation

SUMMARY:

The applicant requests to raise the height of the tower (including antenna installation) from 1,529.3 feet to 1,600 feet. This change is necessitated by the FCC (Federal Communications Commission) mandating that TV stations on the UHF band be moved to the VHF band in order to make room for the wireless industry. No additional wireless communications equipment is being installed on this tower. However, the TV stations that utilize this tower have to move to the VHF band, which utilizes a stacked design as opposed to the current candelabra design to avoid interference amongst the various signals.

Nonconforming Structure Based Upon Setbacks

The structure is nonconforming because it does not meet the setback requirements specified in Section 5.4.4.B of the Zoning Ordinance (Chapter 23), which states:

"In any district where a structure is permitted to be constructed above two (2) stories, an additional setback shall be required from any existing single-family residential use or zoning district. The additional setback shall be two feet (2') for every one foot (1') in height above two (2) stories from the single-family district boundary line or property line, whichever is closer."

Even though other broadcast towers surround the property on the south side of Belt Line Road, those parcels are zoned "SF-E" like the subject site. Therefore, the setbacks still apply. With the proposed expansion, the tower would need to be

3,200 feet away from the nearest single-family zoning district in order to comply. The nearest single-family zoning district is 550 feet to the west. The Ninth Grade Center property is 755 feet to the northwest. The single-family residences are approximately 1,585 feet to the northeast. There is undeveloped, single-family residential property zoned Old Town-Residential located 1,968 feet to the east and "SF-22" (Single-Family Residential – minimum 22,000-square-foot lots) located 555 feet to the north.

HISTORY (HOW DID THE TOWER BECOME NONCONFORMING?):

Prior to 1979: Property was zoned "special use district" for broadcast tower.

Between 1979-1989: The tower was constructed.

2001: The property was rezoned as part of a city-wide rezoning to remove special use zoning as a district. The special use zoning districts for towers were converted to Conditional Use Permits (CUPs). Also, the special height regulations in Section 5.4.4.B were adopted. Even though the use remained conforming with the conversion from a special use zoning district to a CUP in 2001, the structure became nonconforming in terms of height based upon the surrounding residential zoning.

ACTION REQUIRED:

Section 2.2.3.B of the Zoning Ordinance grants the authority to expand a nonconforming structure to the Board. This request is not for a variance. Therefore, the property owner does not have to prove a hardship. In rendering its decision, the Board will have to determine whether or not expansion of the structure height is compatible with or detrimental to property that falls within 3,200 feet of the tower base.

Per Section 2.2.6.D, the concurring vote of four members of the Board is required to decide in favor of the applicant.

ATTACHMENTS:

Maps
Explanation of FCC Broadcast Incentive Auction (provided by applicant)
Design Drawings
Structural Analysis
Tower Inspection Form/Mapping Report

City of Cedar Hill




1 inch = 1,000 feet

0 1,000 Feet

Case PD-69-2018



Map Printed - May 2018
Cedar Hill Planning Department




City of Cedar Hill




1 inch = 1,000 feet

0 1,000 Feet

Case PD-69-2018



Map Printed - May 2018
Cedar Hill Planning Department



FCC Broadcast Incentive Auction

ATC-Milton, Cedar Hill, TX
Telecommunications Facilities

April 25, 2018



What is the FCC Broadcast Incentive Auction

Results of the Auction

Impact on TV stations across the US

Proposed Changes for ATC Milton Tower located in Cedar Hill, TX

What is the FCC Broadcast Incentive Auction

- Approved by Congress and President Obama as part of the "The Middle Class Tax Relief and Job Creation Act of 2012"
- FCC mandated to generate revenue for First Net and the GAO through a spectrum auction
- Wireless industry wanted more low band spectrum to satisfy the ever increasing consumer mobile device demand
- FCC plan to auction all or part of the 600 MHz spectrum currently occupied by TV Ch.32-Ch.51 – Forward Auction
- FCC needed to clear TV stations from the upper UHF band - moving stations to new channels or buying TV licenses back
- FCC created an auction for TV stations to voluntarily sell back their licenses and either go dark permanently, channel share with other TV stations, or move from UHF to the VHF band – Reverse Auction

What is the FCC Broadcast Incentive Auction

- Forward and reverse auctions were run simultaneously 4Q 2016 through 1Q 2017
- Sale of 600Mhz to wireless industry had to generate enough revenue to cover:
 - » Reverse auction buyback of Full Power and Class A TV licenses – Voluntary
 - » FCC cost of running the auction
 - » Reimbursement costs of Full Power and Class A TV stations having to change channels
 - » GAO and First Net funding
- ~2,100 Full Power and Class A stations eligible to either voluntarily or involuntarily participate
- Most complex undertaking ever by the FCC

Results of the Reverse & Forward Auctions

- › Auctions closed April 13, 2017 after multiple auction rounds and downward adjustments to 600 MHz spectrum to be auctioned
- › 70 MHz of the 600 MHz (TV channels 38-51) sold in forward auction for \$19.8b
- › 175 winning TV station licensees in the reverse auction for a total of \$10b to be paid by the FCC to the winners.
 - » 30 stations took lower payments to move to the VHF
 - » 133 stations to remain on the air by channel sharing with stations that did not participate in the auction
 - » 12 stations either going off the air permanently or filed post auction to channel share




Impact on Television Stations Across the US

- Reverse auction winners relinquishing their licenses must shut down by January 20, 2018 or file a waiver for up to two 90-day extensions
- Reverse Auction winners moving from a UHF to VHF channel must cutover by their assigned FCC transition date
- All TV stations that did not participate in the reverse auction were subjected to an involuntary program of possibly having their channel changed – TV Repack
- 957 TV stations are required to change their channel as part of the repack program
- Repack stations must turn off their current channels in accordance with their assigned FCC transition phase


FCC Repack Transition Schedule

- › FCC set a very aggressive 3 year build schedule
- › Repack stations assigned a phase and date where they have to turn off their current channel transmission
- › Lots of debate whether this schedule can be met




Dallas Repack Transition Schedule

- › Dallas TV stations transition in Phase 2
- › June 21, 2019 cutover date
- › **Work to be completed in Summer and Fall 2018**




Milton Tower – Full & Low Power TV Stations



Channel	Cell Size	City of License	AGL	Record Type	HAAT	Power
2-1 (29)	KDTN	DENTON, TX	1518'	DTV-CP	1621'	415 kW DA
11-1 (19)	KTVT	FORT WORTH, TX	1518'	DTV-APP	1719'	465 kW DA
21-1 (18)	KTXA	FORT WORTH, TX	1518'	DTV-CP	1719'	465 kW DA
22-1 (22)	KNAV-LP	DE SOTO, TX	853'	LPD-CP	1052'	15 kW DA
23-1 (23)	KUVN-DT	GARLAND, TX	1496'	DTV-LIC	1696'	1000 kW DA
23-1 (23)	KUVN-DT	GARLAND, TX	1493'	DTV-LIC	1699'	220 kW ND
23-1 (33)	KUVN-DT	GARLAND, TX	1523'	DTV-CP	1726'	1000 kW DA
26-1 (27)	KODF-LD	BRITTON, TX	591'	LPD-LIC	789'	15 kW DA
28-1 (10)	KHPK-LD	DE SOTO, TX	1050'	LPD-LIC	1248'	3 kW DA
31-1 (31)	KGJGL-D	DE SOTO, TX	1083'	LPD-LIC	1281'	8 kW DA
34-1 (34)	KJMJ-LD	DALLAS & MESQUITE, TX	853'	LPD-LIC	1052'	15 kW DA
38-1 (38)	KVFW-LD	FORT WORTH, TX	787'	LPT-LIC	986'	15 kW DA
47-1 (23)	KJXD-TV	GREENVILLE, TX	1518'	DTV-CP	1621'	1000 kW DA
58-1 (21)	KDTX-TV	DALLAS, TX	1518'	DTV-CP	1621'	735 kW DA

ATC – Milton Tower, Cedar Hill, TX



Thank You & Questions?

Peter Starke
Vice President, Broadcast
781-926-4772 (office)
508-878-4876 (mobile)
peter.starke@americantower.com

Cedar Hill, TX – Broadcast Towers (>1,000 Feet AGL)



2 towers 1,000' to 1,250' AGL

9 towers 1,500' to 1,730' AGL

Source: FCC Antenna Structure Registration Data



ATC – Antenna Separation and Placement



Candelabra with 75 ft.
antenna separation




Candelabra with 30 ft.
antenna separation



Proposed stacked
antennas



MECHANICAL SPECIFICATIONS



Proposal No. C-70652-7
 Date 3-May-18
 Call Letters KDTN
 Channel 29
 Frequency 563 MHz
 Antenna Type TUM-C4-AP-14/48H-2-R-B

Preliminary Specifications

Bottom of Stack

With ice TIA-222-G

Height AGL(z) 900 ft (274.3 m)
 Basic Wind Speed 90 m/h (144.8 km/h)

Structure Class II
 Exposure Category C
 Topography Category 1

Design Ice 0.75 in $t_{iz} = 2.10$ in
 Wind Speed w/Ice 30 m/h (48.3 km/h)

Mechanical Specifications

	without ice	with ice	full stack	full stack with ice
Height with Lightning Protector	H4 ft (m)		105.7 ft (32.2m)	
Height less Lightning Protector	H2 51.5 ft (15.7m)		101.7 ft (31m)	
Height of Center of Radiation	H3 25.7 ft (7.8m)		25.7 ft (7.8m)	
Effective Projected Area	(EPA) _S 112.47 ft ² (10.4m ²)	255 ft ² (23.7m ²)	186 ft ² (17.3m ²)	434.1 ft ² (40.3m ²)
Moment Arm	D1 27 ft (8.2m)	28.3 ft (8.6m)	46.2 ft (14.1m)	49 ft (14.9m)
Effective Projected Area	(EPA) _S 92 ft ² (8.5m ²)	195 ft ² (18.1m ²)	92 ft ² (8.5m ²)	195 ft ² (18.1m ²) below tower top
Moment Arm	D3 8.5 ft (2.6m)	8.8 ft (2.7m)	8.5 ft (2.6m)	8.8 ft (2.7m) below lower top
Pole Bury Length	D2 ft (m)	ft (m)	ft (m)	ft (m) below lower top
Weight	W 23400 lb (10.6t)	28390 lb (12.9t)	32200 lb (14.6t)	39320 lb (17.8t)

Antenna designed in accordance with AISC specifications for design of structural steel as prescribed by TIA-222-G

Prepared by: CAB Date: 1-Sep-17 ME: EE:
 Rev. No.7 by: JBC Date: 3-May-18

This document contains proprietary and confidential information of Dielectric. It is to be used solely for the purpose for which it is provided. No disclosure, reproduction, or use of this document or any part of it may be made without the written permission of Dielectric. Mechanical data is based on listed criteria and should be verified by the tower engineer.


Trusted for Decades. Ready for Tomorrow.



**Design Drawings
G-10 Tower Modification
ATC Site: 75253 Milton/Cedar Hill**

INDEX

DESCRIPTION	DWG	REV	DATE	DESCRIPTION	DWG	REV	DATE
GENERAL ARRANGEMENT	D01.00		1/22/2018	HORIZONTAL REPLACEMENT	D05.05		1/24/2018
GENERAL NOTES	D01.01		1/22/2018	SUD-BRACING DETAILS	D05.06		1/24/2018
GENERAL NOTES	D01.03	A	2/23/2018	TOP OF TOWER DETAILS	D05.07		2/8/2018
GENERAL NOTES	D01.03		1/22/2018	TOP OF TOWER DETAILS	D05.08		2/8/2018
TOWER PROFILE	I0X.00		1/24/2018	FLANGE REINFORCEMENT DETAILS	D05.09		2/13/2018
TOWER PROFILE	I0X.01		1/24/2018	COAX ARRANGEMENT FOR 4-3/16" RIGID LINE	D06.00		1/20/2018
TOWER PROFILE	I0X.02	A	2/23/2018	COAX ARRANGEMENT FOR 7-3/16" RIGID LINE	D06.01		1/20/2018
LINEAR APPURTENANCES	I0X.05		1/22/2018	COAX ARRANGEMENT FOR 7-3/16" RIGID LINE	D06.02		1/20/2018
DIAGONAL REPLACEMENT	I0X.01		1/24/2018	GUY #4 ATTACHMENT DETAILS	D08.00		1/23/2018
DIAGONAL REPLACEMENT	I0X.02		1/24/2018	INTERCUFFS & EJECTION TENSIONS	D08.01		2/8/2018
DIAGONAL REPLACEMENT	I0X.03		1/24/2018	MATERIAL LIST	D11.00		2/13/2018
DIAGONAL REPLACEMENT	I0X.04		1/24/2018				



1. The lower is a guyed, triangular, non-insulated, open face structure.
2. The lower was analyzed per Stainless Rigorous Structural Analysis Report 278348 Rev. A, dated 2/12/2018 in accordance with the 2016 IBC and ASCE 22-15, Structural Standard for Antennas Supporting Structures and Antennas, including addenda 1 and 2, dated 2007 and 2009 respectively, for the following analysis parameters while supporting equipment as listed below:
 - Structure Classification II
 - 115 mph ultimate design wind speed with no ice
 - 30 mph nominal design wind speed with 3/4" design ice thickness
 - Exposure C
 - Topographic Category 1
 - 0.11 earthquake spectral response acceleration at short periods (S_a)
 - Earthquake Site Class D
- a. One (1) Dielectric TPU-26GTC-VP-R 4C180 DC SP antenna (KUVN Channel 33 and KSTV Channel 34) and one (1) Dielectric TUM-AP-C4-14/48H-2-R-B (KUVN Channel 33 and KSTV Channel 34) antenna system on top of new 39'-0" tower main extension on top of main tower, fed by one (1) 8'-8 1/8" rigid line and two (2) 7'-3 1/8" rigid lines. (Proposed)
- b. One (1) ERI 1183-8C-2 8-bay panel antenna at the 1380' level, fed by one (1) 6'-1 1/8" rigid line and one (1) 2'-1 1/2" conduit.
- c. One (1) ERI 1183-8C-2 6-bay panel antenna at the 1303' level, fed by one (1) 6'-1 1/8" rigid line and one (1) 2'-1 1/2" conduit.
- d. One (1) MCI 982000 (8-bay with 2 panels each bay) antenna at the 1271' level, fed by one (1) 6'-1 1/8" rigid line.
- e. One (1) SWR 4-bays slot antenna side mount to tower leg at the 1166' level fed by one (1) 4'-1 1/16" rigid line.
- f. One (1) Scale CL-46/HRM/50N Yagi antenna at the 1145' level, fed by one (1) 1-5/8" line.
- g. One (1) Scale CL-46/HRM/50N Yagi antenna at the 1103' level, shares line with Yagi antenna at the 1145' level.
- h. One (1) SBP UPB-C LPTV antenna at the 1085' level, fed by one (1) 4" line.
- i. One (1) SBP UPB-C LPTV antenna at the 1072' level, fed by one (1) 3" line.
- j. One (1) Dielectric THA-C2 antenna at the 1072' level, fed by one (1) 3" line.
- k. One (1) ProScan JHJ ENG antenna at the 995' level, fed by one (1) 1-1/4" line and one (1) 7/8" line.
- l. One (1) Micro Communication Ch30 and Ch 60 side mounted antenna at the 950' level, fed by one (1) 4" line.
- m. One (1) Telenav AN15100F6-7 antenna on platform handrail mount at the 905.5' level, no associated line.
- n. Two (2) 18"x12" junction boxes, one (1) 5412 ESS242010 unit, one (1) 24"x24"x14" junction box and one (1) 48"x24" junction box at the 899' level, fed by two (2) 7/8" lines.
- o. One (1) DB420 ME-E dipole antenna at the 892.5' level, fed by one (1) 7/8" line.
- p. One (1) 8' wide, three-sided platform at the 882' level.
- q. One (1) MCI 986138 (8-bay with 2 panels each bay) antenna at the 840' level, fed by one (1) 4" line and one (1) future 4" line.
- r. One (1) MCI 986138 (8-bay with 2 panels each bay) antenna at the 793' level, fed by one (1) 3" line.
- s. One (1) ERI SHPX-BAC6-HW FM antenna at the 745' level, fed by one (1) 3-1/8" rigid line.
- t. Six (6) AN1430-01 antennas and twenty-four (24) BMAX-BST-AU-ODU units at the 655' level, fed by twenty-four (24) 6/8" lines.
- u. One (1) MCI 9851938 (8-bay with 2 panels each bay) antenna at the 581' level, fed by one (1) 3" line.
- v. One (1) 4' Yagi antenna at the 577.5' level, fed by one (1) 7/8" line.
- w. One (1) DB420ME-E dipole antenna at the 566.5' level, fed by one (1) 7/8" line.
- x. One (1) 10' grid dish antenna at the 528' level, fed by one (1) 7/8" line.
- y. One (1) DB224-E dipole antenna, one (1) 20' dipole antenna and one (1) 10' grid dish antenna at the 500' level, fed by one (1) 7/8" line and one (1) 1-1/4" line.
- z. One (1) 12' ice shield at the 410' level.

aa. One (1) 3' Yagi antenna at the 405' level, fed by one (1) 7/8" line.
 bb. One (1) 12' standard dish antenna at the 400' level, fed by one (1) 7/8" line.
 cc. One (1) 6' ice shield at the 378' level.
 dd. One (1) 10' grid dish antenna at the 382' level, fed by one (1) 7/8" line.
 ee. One (1) 8' grid dish antenna at the 378' level, fed by one (1) 7/8" line.
 ff. One (1) 8' standard dish antenna and one (1) 10' grid antenna at the 362' level, fed by one (2) 7/8" lines.
 gg. One (1) RFS PD200 omni antenna at the 360' level, fed by one (1) 7/8" line.
 hh. One (1) 8' HP dish antenna at the 352.6' level, fed by one (1) EW63 cable.
 ii. One (1) 2' grid dish antenna at the 334' level, fed by one (1) 1-5/8" line.
 jj. One (1) 10' grid dish antenna at the 333' level, fed by one (1) 1-5/8" line.
 kk. Two (2) 8' standard dish antennas at the 330' level, fed by two (2) 1/2" lines.
 ll. One (1) 10' grid dish antenna at the 326' level, fed by one (1) 7/8" line.
 mm. One (1) RFS DA12-65AC dish antenna at the 326' level, fed by one (1) EW63 cable.
 nn. One (1) 12' ice shield at the 306' level.
 oo. One (1) 8' standard dish antenna at the 300' level, no associated line.
 pp. One (1) UHDX-69-53A/LP dish antenna at the 300' level, fed by one (1) EW63 cable.
 qq. One (1) RFS DA12-65AC dish antenna at the 276' level, fed by one (1) EW63 cable.
 rr. Two (2) 6' ice shields at the 267' level.
 ss. Two (2) RFS SBX2-107NEC HP dishes at the 262' level, fed by four (4) RFS lines.
 tt. Three (3) CG8 X7C-605 and three (3) Jaybeam PCSX06-18-0 antennas; three (3) LGP18061 TTA units on sector frames at the 252' level, fed by nine (9) 1-5/8" lines.
 uu. One (1) 3' standard dish antenna at the 224' level, fed by one (1) 0-16" line.
 vv. One (1) 12' ice shield at the 212.5' level.
 ww. One (1) 12' grid dish antenna at the 203' level, fed by one (1) 7/8" line.
 xx. One (1) Scale CAT-410 Yagi antenna at the 200' level, fed by one (1) 7/8" line.
 yy. One (1) PLB-85 6' standard MW dish antenna at the 200' level, fed by one (1) EW63 cable.
 zz. One (1) 6' standard dish antenna at the 190' level, fed by one (1) 1/2" line.
 aaa. One (1) 8' grid dish antenna at the 188' level, fed by one (1) 7/8" line.
 bbb. One (1) 10' grid dish antenna at the 170' level, fed by one (1) 7/8" line.
 ccc. One (1) 2' Yagi antenna at the 163' level, fed by one (1) 1/2" line.
 ddd. One (1) 4' standard dish antenna and two (2) TTA units at the 131 level, fed by one (1) 5-5/8" line.
 eee. One (1) 2' Yagi antenna at the 107' level, fed by one (1) 3/8" line.
 fff. One (1) 4' standard dish antenna at the 131 level, fed by one (1) 5-5/8" line.
 ggg. One (1) 10' Omni antenna at the 70' level, fed by one (1) 7/8" line.
 hhh. One (1) 1-1/4" conduit to 1443' level.
 iii. One (1) 1-1/2" line support conduit (assumed) to level 1072'.
 jjj. One (1) 1-1/2" line support conduit (assumed) to level 650'.
 kkk. One (1) 3/4" line support conduit (assumed) to level 500'.
 ll. One (1) 1-1/2" line support conduit to level 252'.
 mmm. One (1) 1-1/4" line support conduit to level 610'.
 nnn. One (1) 1-1/2" line support conduit (assumed) to level 325'.
 ooo. One (1) two man, double-deck elevator to level 1455'.
 ppp. One (1) 3/4" conduit containing control circuits for item above.
 qqq. One (1) lighting system with 3" conduit to lower top.
 rrr. One (1) climbing ladder without safety cable to lower top.

 STAINLESS <small>STEEL</small> <small>Welding & Fabricating</small> <small>Services</small> <small>Inc.</small>		GENERAL NOTES DALLAS, TX	<small>THIS DRAWING IS THE PROPERTY OF STAINLESS STEEL FABRICATING CO. INC. AND IS TO BE USED ONLY FOR THE SPECIFIED CONTRACT. IT IS NOT TO BE COPIED OR USED FOR ANY OTHER PURPOSE. IT IS THE PROPERTY OF THE COMPANY AND MUST BE RETURNED UPON REQUEST.</small>	
PROJECT NO. 273749	DRAWING NO. D01.01			
PREPARED BY CHUCK CO REV. 1/10/01	RC. 1/10/01	RECEIVED BY ROBERT L. S.		
				DATE 1/10/01

4. In order for the tower to achieve a 115 mph ultimate design wind speed with no ice, and a 50 mph nominal design wind speed with 3/4" design ice thickness in accordance with the 2015 IBC and ANSI/TIA 222-G, the following modifications are required:

- a. Install two (2) tower sections totaling approximately 30'
- b. Replace guy level 4 with new 1-0716" dia. GR2 guy wires.
- c. Install additional horizontal sub-bracing at the midpoints of the following bays:

Location	No. of bays
1108.8' - 1153.8'	6
1086.3' - 1093.8'	1
1063.8' - 1071.8'	1

d. Replace existing diagonal braces with new, higher capacity members at the following bays:

Location	No. of bays
1011.3' - 1033.8'	3
838.8' - 853.8'	2
608.8' - 823.8'	2
716.8' - 776.8'	8
658.8' - 666.3'	6
613.8' - 621.3'	1
676.3' - 606.3'	4
631.3' - 563.8'	9
441.3' - 463.8'	3
388.8' - 366.3'	1
366.3' - 361.3'	2
246.3' - 343.8'	13
216.3' - 238.8'	3
178.8' - 208.8'	4
141.3' - 156.3'	2
738.1' - 133.8'	6

e. Replace existing horizontal braces with new, higher capacity members at the following bays:

Location	No. of levels
1033.8' - 1041.3'	2
201.3' - 208.8'	2
116.8' - 133.8'	3

f. Adjust the initial guy tensions to the following values at 60 degrees F:

Level	Tension (kips)
1B	27680
2B	28700
3B	41520
4B	41520
6B	38880
5B	41600
7B	60180
8B	38880

g. Reinforce existing leg flanges and replace existing flange bolts with new, higher capacity bolts at one (1) level - Elevation 1488'.

5. The design of the tower modifications above has been based upon Stainless Rigorous Structural Analysis Report 278346, dated 12/05/2017. The details contained within this design drawing package, including the information and data intended to be used as shop and visual fabrication drawings. The Contractor shall field verify all dimensions, elevations and existing site conditions and notify Stainless immediately of any site discrepancies or variances. Contractor shall not scale dimensions from the design drawings. It shall be the responsibility of the Contractor to ensure proper fit-up of the tower modifications in-situ. All work shall be done in accordance with the design drawing package shall be performed by a qualified contractor(s) with a minimum of 6 years experience in tower and foundation construction.

6. All material shall be in accordance with the notes, specifications and drawings. All deviations and substitutions must be approved by a registered Professional Engineer in the state where the work is being done and submitted to Stainless for approval prior to installation. The Contractor shall furnish satisfactory evidence as to the kind and quality of the materials and equipment being substituted. Contractor shall also be responsible for obtaining all necessary permits, licenses and any other requirements for the construction. Submit all necessary calculations for substitutions and design details.

7. Contractor shall observe safe construction practices and shall be responsible for temporary support of the structure, including proper and adequate bracing to the tower and excavation work during the installation process. Adequately designed temporary support shall be installed before any tower component is removed and replaced. All means and methods of construction, including construction and soil pressure loads, shall be properly calculated and documented by the Contractor.

8. If the construction activities require a rigging plan per the requirements of ANSI/ASME A10.46 and ANSI/TIA-322-2016, rigging plan shall be developed by a Qualified Person, submitted to the Owner for review and implementation prior to construction. The Owner shall coordinate Class IV rigging plans with a Qualified Engineer for a structural analysis of the structure considering the construction loading. A properly detailed rigging plan shall include, at a minimum, a review of the following:

- a. Operational and non-operational construction loads.
- b. Equipment used, and Supporting structure.
- c. Construction sequence and durations.

9. Stainless assumes no responsibility for the structural adequacy of the tower if any modifications are made to the tower by anyone other than Stainless. Others are and shall have no liability whatsoever to owner or to others for any work performed by any persons other than Stainless in connection with the implementation of any structural changes or modifications not specifically addressed within this design drawing package. Owner acknowledges and agrees that any riggers, erectors or subcontractors retained or employed by owner shall be responsible to owner and others for the quality of work performed by them, and that Stainless shall have no liability or responsibility whatsoever as a result of any negligence or breach of contract by such rigger, erector or subcontractor.


10. The modification drawings contained herein are based on the assumption that the tower has been properly installed and maintained, including, but not limited to the following:

- a. Proper alignment and plumbness.
- b. Correct bolt tightness.
- c. No significant deterioration or damage to any component.

11. The design of the tower modifications are based on all existing antennas, antenna mounting pedestals and lines on candelabra being removed.

12. All galvanizing remediation is to be in accordance with American Tower Corporation Standard Specifications for Tower Sites, dated 1/23/2017 and ASTM A780 Standard Practice for Repair of Damage and Uncoated Areas of Hot-Dip Galvanized Coatings.

PREPARED	RE	1/22/18
CHECKED	RE	01/22/18
ENGINEER	RE	2018
PROJECT	RE	278346
DRAWING	RE	278346
NUMBER	RE	01/22/18



NOTICE: THE INFORMATION CONTAINED HEREIN IS UNCLASSIFIED
DATE 12/28/2018 BY [Signature]

APPLICABLE CODES AND STANDARDS

Use latest editions of the following Codes and Standards unless noted otherwise.

- ANSI/TIA-222-G 2006 Structural Standards for Antenna Supporting Structures and Equipment, including ANSI/TIA-222-G-2006, ANSI/TIA-222-G-2006
- ANSI/IEEE A10.4 Criteria for Safety Practices Related to the Installation, Alteration, and Maintenance of Communication Structures, ANSI/TIA-322 Loading, Analysis and Design Criteria Related to the Installation, Alteration and Maintenance of Communication Structures.
- AISC Manual of Steel Construction.
- RCSC Specification for Structural Joints Using ASTM A325 or A490 Bolts.
- AISI/ASCE 31-05 Specification for Structural Concrete.
- ACI 318 Building Code Requirements for Structural Concrete.
- ACI 315 Details and Detailing of Concrete Reinforcement.
- CRSI Manual of Standard Practice.
- ASTM C260 Standard Specification for Air-Entraining Admixtures for Concrete.
- ASTM C494 Standard Specification for Chemical Admixtures for Concrete.
- ASTM A35 Standard Specification for Carbon Structural Steel.
- ASTM A572 Standard Specification for High-Strength Low-Alloy Columbium-Vanadium Structural Steel.
- ASTM A325 Standard Specification for Structural Bolts, Steel, Heat Treated, 120/105 kip Minimum Tensile Strength.
- ASTM A184 Standard Specification for Carbon and Alloy Steel Nuts for Bolts and Screws, Heat Treated, and for Service at Room Temperature.
- ASTM F436 Standard Specification for Hardened Steel Washers.
- ASTM A123 Standard Specification for Zinc (Hot-Dip) Galvanized Coatings on Iron and Products.
- ASTM A167 Standard Specification for Zinc Coating (Hot-Dip) on Iron and Steel Products.
- ASTM A780 Standard Practice for Repair of Damage and Uncoated Areas of Hot-Dip Galvanized Coatings.
- ASTM A616 Standard Specification for Deformed and Plain Carbon Steel Bars for Concrete Reinforcement.

STRUCTURAL STEEL

- The fabrication and erection of structural steel shall conform to the AISC Manual of Steel Construction.
- Reinforcing designed or uncoupled areas of galvanized coatings in accordance with ASTM A780.
- Locking ANCO style nuts shall be installed on all bolts unless noted otherwise.
- All A325 high strength bolts shall be tightened by the "anug tightening" method as specified in the RCSC Specification for Structural Joints Using ASTM A326 Bolts unless noted otherwise on the design drawings.
- Material grades shall be as follows:
 - Bolts - A325X and A490X
 - U-Bolts - A307 min.
 - Round Bars - A572 Gr.50
 - Plates and angles - A36
 - Channels - A572 Grade 50
 - Guy strands - ASTM A686 Grade 2

INSTALLING GUYS AND PLUMBING LINES


- The lower is designed for initial tension as specified in the erection drawings. It is important that the guys be tensioned accurately to assure the stiffness of the tower.
- Uneven terrain, temperature, plumbness of lower and wind are factors which affect guy tensions. If the lower site is level and anchor distances are equal, the tensions in all three guys at a level will be equal when the tower is plumb. If the terrain of the lower site is uneven, the guys are not perfectly symmetrical and tensions in guys vary in the three directions. For this reason initial guy tensions are specified in one direction only. The tower should be plumbed with the specified tension in the specified direction.
- Wind load on lower and guys changes the tension in all guys; therefore, plumb the tower in calm weather only.

- In changing out guys, work should proceed in one guy direction at a time. A temporary guy must be installed before removing existing guy. It is the contractor's responsibility to insure the temporary guy and its connections are adequately designed for the loads imposed on it.
- The plumbing of a lower or checking alignment of a lower should be performed in accordance with Annex J of ANSI/TIA 222-G.


TOWER PAINTING

- The tower modifications shall be painted with International Orange and White in accordance with FAA Specifications. This includes all lower structural members and coaxial cable, condule and other cables attached to the face of the tower. It does not include the lower ladder nor condule and cables located in the interior of the tower. Paint shall be supplied by the Contractor.
- Painting can be performed in either of two ways:
 - On the ground prior to erection
 - After the tower modifications have been installed. If Method 'a' is followed, all paint damage shall be repaired and touched up after assembly and erection of the tower modifications.
- Painting shall not be performed when the temperature is below 45° Fahrenheit or when the steel is wet from rain or condensation.
- All paint shall be applied on clean surfaces. Paint shall be applied smoothly, to a uniform thickness and without voids, pin holes, brush marks, laps, runs or other defects.

PREPARED BY	RECEIVED BY	DATE
CHIEF ENGINEER	GR.	2/9/08
PROJECT NUMBER	PROJECT NUMBER	278349
DATE	DATE	DO1.03
PROJECT DESCRIPTION: 500 ft. Cell Tower, Dallas, TX		
 GENERAL NOTES DALLAS, TX		
 <small>THE STATE OF TEXAS PROFESSIONAL ENGINEER LICENSING BOARD DOES NOT ISSUE OR REISSUE ANY LICENSES, OR ANY OTHER DOCUMENTS TO ANYONE WHO IS NOT A REGISTERED PROFESSIONAL ENGINEER IN THE STATE OF TEXAS. THE STATE OF TEXAS PROFESSIONAL ENGINEER LICENSING BOARD DOES NOT ISSUE OR REISSUE ANY LICENSES, OR ANY OTHER DOCUMENTS TO ANYONE WHO IS NOT A REGISTERED PROFESSIONAL ENGINEER IN THE STATE OF TEXAS.</small>		



PAINT SCHED.	HORIZONTAL REPLACEMENT	TOWER ELEVATION	DIAGONAL REPLACEMENT								
 3/11/08	 STAINLESS A Division of FISH VOLSTEN 200 North Warner Road, Suite 215 King of Prussia, PA 19406 TOWER PROFILE DALLAS, TX	*						PREPARED BY	RE	12418	
		*						CHECKED BY	GF	2/8/18	
		*						ENGINEER REVIEW	PAC	2/12/18	
		*						PROJECT NUMBER			278349
		*						DRAWING NUMBER			D04.00
		REV	BY	DATE	REVISION DESCRIPTION			D.CK	DATE	E.CK	DATE
K278349.dwg (K278349_D04.00_TOWER_PROFILE.dwg)											




NOTE:


NOTE:


1. PAINT NEW TOWER MATERIAL TO
MATCH EXISTING TOWER BANDS

INSTALL TWO (2) NEW TOWER SECTIONS
TOTALING APPROXIMATELY 39',
SEE PAGE D05.07 & D05.08



PAINT SCHED.	TOWER EXTENSION	TOWER ELEVATION	A HORIZONTAL SUB-BRACING AND FLANGE REINFORCEMENT								
 STAINLESS A BUSINESS OF FOH VELDHOEN 300 High Warner Road, Suite 215 King of Prussia, PA 19406 TOWER PROFILE DALLAS, TX	*					PREPARED BY	RE	1/24/18			
	*					CHECKED BY	GH	2/8/18			
	*					ENGINEER REVIEW	PCC	2/12/18			
	*					PROJECT NUMBER	278349				
	*					DRAWING NUMBER	D04.02				
	*					REV BY	DATE	REVISION DESCRIPTION	D.CK	DATE	E.CK
THIS DRAWING IS THE PROPERTY OF STAINLESS AND IS TRANSMITTED IN CONFIDENCE. IT IS THE PROPERTY OF STAINLESS AND IS TO BE KEPT IN WHOLE OR IN PART, OF THE DESIGN AND DETAILS CONTAINED HEREIN IS PROHIBITED WITHOUT THE PRIOR WRITTEN PERMISSION OF STAINLESS.											
K1278349.dwg1278349_D04.00_TOWER_PROFILE.dwg											





ELEVATION VIEW

DIAGONAL REPLACEMENTS

ELEVATION	BAYS	(A)	(B)	MAXIMUM FACTORED TENSION LOADS
73.8' - 96.3'	3	1" DIAMETER (A572 GRADE 50)	(2) 5/8" DIA. BOLTS (A490X)	35.0 KIPS SEE NOTE 2
96.3' - 111.3'	2	7/8" DIAMETER (A572 GRADE 50)	(2) 5/8" DIA. BOLTS (A325X)	27.0 KIPS SEE NOTE 2
111.3' - 133.8'	3	1" DIAMETER (A572 GRADE 50)	(2) 5/8" DIA. BOLTS (A490X)	35.0 KIPS SEE NOTE 2
141.3' - 156.3'	2	1-1/4" DIAMETER (A572 GRADE 50)	(2) 7/8" DIA. BOLTS (A325X)	55.0 KIPS SEE NOTE 2
178.8' - 193.8'	2	1-1/4" DIAMETER (A572 GRADE 50)	(2) 7/8" DIA. BOLTS (A325X)	55.0 KIPS SEE NOTE 2
216.3' - 223.8'	1	1" DIAMETER (A572 GRADE 50)	(2) 5/8" DIA. BOLTS (A490X)	35.0 KIPS SEE NOTE 2
223.8' - 236.8'	2	7/8" DIAMETER (A572 GRADE 50)	(2) 5/8" DIA. BOLTS (A325X)	27.0 KIPS SEE NOTE 2
246.3' - 253.8'	1	7/8" DIAMETER (A572 GRADE 50)	(2) 5/8" DIA. BOLTS (A325X)	27.0 KIPS SEE NOTE 2
253.8' - 268.8'	2	1" DIAMETER (A572 GRADE 50)	(2) 3/4" DIA. BOLTS (A325X)	35.0 KIPS SEE NOTE 2
268.8' - 283.8'	2	1-1/4" DIAMETER (A572 GRADE 50)	(2) 3/4" DIA. BOLTS (A325X)	55.0 KIPS SEE NOTE 2

TOWER MUST BE ADEQUATELY BRACED BEFORE REMOVING ANY EXISTING MEMBER

NOTES:

1. REPLACE ONLY ONE TENSION ROD MEMBER ON ONE FACE AT A TIME.
2. DESIGN END PAD CONNECTIONS TO DEVELOP THE DESIGN TENSILE STRENGTH OF THE TENSION RODS PER ANSI/TIA 222-G.




STAINLESS
A Business of FCH Worldwide
200 North Washington Suite 200
Longmont, CO 80501

DIAGONAL REPLACEMENT
DALLAS, TX

THIS DRAWING IS THE PROPERTY OF STAINLESS AND TRANSMITTED IN CONFIDENCE, AND THE REPRODUCTION, USE OR DISCLOSURE, IN WHOLE OR IN PART, OF THE DESIGN AND DETAILS CONTAINED HEREIN IS PROHIBITED WITHOUT THE PRIOR WRITTEN PERMISSION OF STAINLESS.

REV	BY	DATE	REVISION DESCRIPTION	D.CN	DATE	E.CN	DATE	PREPARED BY	RE	12418
								CHECKED BY	GA	2/9/18
								ENGINEER REVIEWED	PEC	2/12/18
								PROJECT NUMBER	278349	
								DRAWING NUMBER	D05.01	

K:\278349\dwg\278349_D05.01_1c_D05.03_Diagonal_Replacement.dwg



ELEVATION VIEW

DIAGONAL REPLACEMENTS


ELEVATION	BAYS	(A)	(B)	MAXIMUM FACTORED TENSION LOADS
283.8' - 298.8'	2	1-1/4" DIAMETER (A572 GRADE 50)	(2) 7/8" DIA. BOLTS (A325X)	55.0 KIPS SEE NOTE 2
366.3' - 373.8'	1	1-1/4" DIAMETER (A572 GRADE 50)	(2) 7/8" DIA. BOLTS (A325X)	55.0 KIPS SEE NOTE 2
373.8' - 381.3'	1	1-1/4" DIAMETER (A572 GRADE 50)	(2) 3/4" DIA. BOLTS (A490X)	55.0 KIPS SEE NOTE 2
388.8' - 396.3'	1	1" DIAMETER (A572 GRADE 50)	(2) 3/4" DIA. BOLTS (A325X)	35.0 KIPS SEE NOTE 2
441.3' - 463.8'	3	7/8" DIAMETER (A572 GRADE 50)	(2) 5/8" DIA. BOLTS (A325X)	27.0 KIPS SEE NOTE 2
576.3' - 583.8'	1	1-1/4" DIAMETER (A572 GRADE 50)	(2) 7/8" DIA. BOLTS (A325X)	55.0 KIPS SEE NOTE 2
583.8' - 598.8'	2	1-1/4" DIAMETER (A572 GRADE 50)	(2) 3/4" DIA. BOLTS (A490X)	55.0 KIPS SEE NOTE 2
598.8' - 606.3'	1	1" DIAMETER (A572 GRADE 50)	(2) 3/4" DIA. BOLTS (A325X)	35.0 KIPS SEE NOTE 2
613.8' - 621.3'	1	1" DIAMETER (A572 GRADE 50)	(2) 5/8" DIA. BOLTS (A490X)	35.0 KIPS SEE NOTE 2
658.8' - 673.8'	2	1" DIAMETER (A572 GRADE 50)	(2) 5/8" DIA. BOLTS (A490X)	35.0 KIPS SEE NOTE 2

TOWER MUST BE ADEQUATELY
BRACED BEFORE REMOVING
ANY EXISTING MEMBER

NOTES:

1. REPLACE ONLY ONE TENSION ROD MEMBER ON ONE FACE AT A TIME.
2. DESIGN END PAD CONNECTIONS TO DEVELOP THE DESIGN TENSILE STRENGTH OF THE TENSION RODS PER ANSI/TIA 222-G.

 STAINLESS <small>A BUSINESS OF FDH VELVETTE, 220 North Water Street, Suite 215 Milwaukee, WI 53212</small>	DIAGONAL REPLACEMENT								PREPARED BY	RE	12/18				
	DALLAS, TX								CHECKED BY	GA	2/9/18				
								ENGINEER REVIEW	PEC	2/12/18					
								PROJECT NUMBER	278349						
						REV. BY	DATE	REVISION DESCRIPTION	D.CK	DATE	E.CK	DATE	DRAWING NUMBER	D05.02	
<small>THIS DRAWING IS THE PROPERTY OF STAINLESS AND TRANSMITTED IN CONFIDENCE. AND THE REPRODUCTION, USE OR DISCLOSURE, IN WHOLE OR IN PART, OF THE DESIGN AND DETAILS CONTAINED HEREIN IS PROHIBITED WITHOUT THE PRIOR WRITTEN PERMISSION OF STAINLESS.</small>															
<small>K278349.dwg\278349_D05.01_to_D05.02_Diagonal_Replacement.dwg</small>															



ELEVATION VIEW


DIAGONAL REPLACEMENTS				
ELEVATION	BAYS	(A)	(B)	MAXIMUM FACTORED TENSION LOADS
673.8' - 696.3'	3	1" DIAMETER (A572 GRADE 50)	(2) 3/4" DIA. BOLTS (A325X)	35.0 KIPS SEE NOTE 2
718.8' - 733.8'	2	1-1/4" DIAMETER (A572 GRADE 50)	(2) 7/8" DIA. BOLTS (A325X)	55.0 KIPS SEE NOTE 2
733.8' - 756.8'	3	1-1/4" DIAMETER (A572 GRADE 50)	(2) 3/4" DIA. BOLTS (A490X)	55.0 KIPS SEE NOTE 2
756.3' - 763.8'	1	1" DIAMETER (A572 GRADE 50)	(2) 3/4" DIA. BOLTS (A325X)	35.0 KIPS SEE NOTE 2
763.8' - 771.3'	1	1" DIAMETER (A572 GRADE 50)	(2) 5/8" DIA. BOLTS (A490X)	35.0 KIPS SEE NOTE 2
771.3' - 778.3'	1	7/8" DIAMETER (A572 GRADE 50)	(2) 5/8" DIA. BOLTS (A325X)	27.0 KIPS SEE NOTE 2
808.8' - 823.8'	2	7/8" DIAMETER (A572 GRADE 50)	(2) 5/8" DIA. BOLTS (A325X)	27.0 KIPS SEE NOTE 2
838.8' - 853.8'	2	1-1/4" DIAMETER (A572 GRADE 50)	(2) 3/4" DIA. BOLTS (A490X)	55.0 KIPS SEE NOTE 2
1011.3' - 1033.8'	3	7/8" DIAMETER (A572 GRADE 50)	(2) 5/8" DIA. BOLTS (A325X)	27.0 KIPS SEE NOTE 2

TOWER MUST BE ADEQUATELY
BRACED BEFORE REMOVING
ANY EXISTING MEMBER

NOTES:

1. REPLACE ONLY ONE TENSION ROD MEMBER ON ONE FACE AT A TIME.
2. DESIGN END PAD CONNECTIONS TO DEVELOP THE DESIGN TENSILE STRENGTH OF THE TENSION RODS PER ANSI/TIA 222-G.

	STAINLESS <small>A Business of KELLY VENTURE, 2000 North Royal Road, Suite 210 King of Prussia, PA 19406</small>								PREPARED BY	RE	1/24/18		
DIAGONAL REPLACEMENT DALLAS, TX									CHECKED BY	GA	2/9/18		
<small>THIS DRAWING IS THE PROPERTY OF STAINLESS AND IS TRANSMITTED IN CONFIDENCE, AND THE REPRODUCTION, USE OR DISCLOSURE, IN WHOLE OR IN PART, OF THE DESIGN AND DETAILS CONTAINED HEREIN IS PROHIBITED WITHOUT THE PRIOR WRITTEN PERMISSION OF STAINLESS.</small>		REV	BY	DATE	REVISION DESCRIPTION			D.CK	DATE	E.CK	DATE	PROJECT NUMBER	278349
		K3278349\dwg\278349_D05.01_to_D05.03_Diagonal_Replacement.dwg											
												DRAWING NUMBER	D05.03



ELEVATION VIEW

NOTES:

1. REPLACE ONLY ONE TENSION ROD MEMBER ON ONE FACE AT A TIME.
2. ALL CONNECTIONS SHALL BE DESIGNED TO DEVELOP THE MAXIMUM FACTORED LOADS FOR TENSION AND COMPRESSION.

TOWER MUST BE ADEQUATELY BRACED BEFORE REMOVING ANY EXISTING MEMBER

DIAGONAL REPLACEMENTS								
ELEVATION	BAYS	INNER	① OUTER	②	③	④	⑤	MAXIMUM FACTORED LOADS
193.8' - 208.8'	2	L3 x 2-1/2 x 1/4 (A36)	L3 x 2-1/2 x 1/4 (A36)	(2) 5/8" DIA. BOLTS (A325X)	1/2" PLATE (A36)	(2) 5/8" DIA. BOLTS (A325X) + 1/2" THK. SPACER (A36)	N/A	60.0 KIPS SEE NOTE 2
298.8' - 313.8'	2	L3 x 2-1/2 x 1/4 (A36)	L3 x 2-1/2 x 1/4 (A36)	(2) 7/8" DIA. BOLTS (A325X)	1/2" PLATE (A36)	(2) 5/8" DIA. BOLTS (A325X) + 1/2" THK. SPACER (A36)	N/A	60.0 KIPS SEE NOTE 2
313.8' - 343.8'	4	L3 x 2-1/2 x 1/4 (A36)	L3 x 2-1/2 x 1/4 (A36)	(2) 1" DIA. BOLTS (A325X)	1/2" PLATE (A36)	(2) 5/8" DIA. BOLTS (A325X) + 1/2" THK. SPACER (A36)	(2) 5/8" DIA. BOLTS (A325X)	60.0 KIPS SEE NOTE 2
531.3' - 546.3'	2	L3 x 2-1/2 x 1/4 (A36)	L3 x 2-1/2 x 1/4 (A36)	(2) 1" DIA. BOLTS (A325X)	1/2" PLATE (A36)	(2) 5/8" DIA. BOLTS (A325X) + 1/2" THK. SPACER (A36)	(2) 5/8" DIA. BOLTS (A325X)	60.0 KIPS SEE NOTE 2
546.3' - 553.8'	1	L3 x 2-1/2 x 1/4 (A36)	L3 x 2-1/2 x 1/4 (A36)	(2) 1" DIA. BOLTS (A325X)	1/2" PLATE (A36)	(2) 5/8" DIA. BOLTS (A325X) + 1/2" THK. SPACER (A36)	N/A	60.0 KIPS SEE NOTE 2



STAINLESS[®]

A Division of FCI Worldwide
200 North Franklin, Suite 205
King of Prussia, PA 19406


DIAGONAL REPLACEMENT
DALLAS, TX

THIS DRAWING IS THE PROPERTY OF STAINLESS AND IS TRANSMITTED IN CONFIDENCE, AND THE REPRODUCTION, USE OR DISCLOSURE, IN WHOLE OR IN PART, OF THE DESIGN AND DATA IT CONTAINS HEREBY IS PROHIBITED WITHOUT THE PRIOR WRITTEN PERMISSION OF STAINLESS.

PREPARED BY	RE	12/18
CHECKED BY	GD	2/9/18
ENGINEER REVIEW	JCC	2/12/18
PROJECT NUMBER	278349	
DRAWING NUMBER	D05.04	


REV. BY DATE REVISION DESCRIPTION D.C.K. DATE E.C.K. DATE

K278349dwg278348_D05.04_Diagonal_Replacement.dwg



ELEVATIONS	# BAYS	LEG Ø	C-CLAMP ASS'Y	C-CLAMP	CENTER PLATE	U-BOLT	SUB-BRACE SIZE	MAX. FACTORED COMPRESSION LEG LOADS
1063.8' - 1071.3'	1	$5\frac{5}{8}$ "	$\frac{3}{8}$ " PLATE (A36)	$\frac{3}{8}$ " PLATE (A36)	$\frac{3}{8}$ " PLATE (A36)	$\frac{3}{8}$ " DIA. (A307)	L 2 1/2 x 2 1/2 x 1/4 (A36)	808.0 KIPS
1086.3' - 1093.8'	1	$5\frac{5}{8}$ "	$\frac{3}{8}$ " PLATE (A36)	$\frac{3}{8}$ " PLATE (A36)	$\frac{3}{8}$ " PLATE (A36)	$\frac{3}{8}$ " DIA. (A307)	L 2 1/2 x 2 1/2 x 1/4 (A36)	784.0 KIPS
1108.8' - 1123.8'	2	$5\frac{1}{8}$ "	$\frac{3}{8}$ " PLATE (A36)	$\frac{3}{8}$ " PLATE (A36)	$\frac{3}{8}$ " PLATE (A36)	$\frac{3}{8}$ " DIA. (A307)	L 2 1/2 x 2 1/2 x 1/4 (A36)	702.0 KIPS
1123.8' - 1153.8'	4	$5\frac{1}{8}$ "	$\frac{3}{8}$ " PLATE (A36)	$\frac{3}{8}$ " PLATE (A36)	$\frac{3}{8}$ " PLATE (A36)	$\frac{3}{8}$ " DIA. (A307)	L 2 1/2 x 2 1/2 x 1/4 (A36)	702.0 KIPS

NOTE: DESIGN SUB-BRACING CONNECTIONS PER ANSI/TIA 222-G BASED UPON THE MAXIMUM COMPRESSION LEG LOADS SHOWN.




A BUSINESS OF EDI VITRONICS
220 North Warner Road, Suite 210
King of Prussia, PA 19406

SUB-BRACING DETAILS

DALLAS, TX

THIS DRAWING IS THE PROPERTY OF STAINLESS AND IS TRANSMITTED IN CONFIDENCE, AND THE REPRODUCTION, USE OR Disclosure, WHOLE OR IN PART, OF THE DESIGN AND DETAILS CONTAINED HEREIN IS PROHIBITED WITHOUT THE PRIOR WRITTEN PERMISSION OF STAINLESS.

REV	BY	DATE	REVISION DESCRIPTION	ACK	DATE	ACK	DATE	PREPARED BY	RE	12448
								CHECKED BY	GA	2/9/18
								ENGINEER REVIEW	PCC	2/12/18
								PROJECT NUMBER	278349	
								DRAWING NUMBER	D05.06	



STAINLESS

A Business of FDH Ventures,
200 North Wacker Road, Suite 215
Chicago, IL 60606, USA 60606

TOP OF TOWER DETAILS
DALLAS, TX

THIS DRAWING IS THE PROPERTY OF STAINLESS AND IS TRANSMITTED IN CONFIDENCE. AND THE REPRODUCTION, USE, OR DISCLOSURE, IN WHOLE OR IN PART, OF THE DESIGN AND DETAILS CONTAINED HEREIN IS PROHIBITED WITHOUT THE PRIOR WRITTEN PERMISSION OF STAINLESS.

K478349.dwg\278349_D05.07_D05.08_Tower_Top.dwg

REV	BY	DATE	REVISION DESCRIPTION	D.C.K.	DATE	E.C.K.	DATE	PREPARED BY	RE	2016
								CHECKED BY	GR	2/9/18
								ENGINEER REVIEW	PLC	2/12/18
								PROJECT NUMBER	278349	
								DRAWING NUMBER	D05.07	

NOTE:

NOTE:
1. ALL BOLTS IN THIS BAY, EXCEPT FOR
STITCH BOLTS, SHALL BE TIGHTENED
USING "TURN OF THE NUT" METHOD.

PROPOSED STACK ANTENNA: TOP MOUNTED
ONE (1) DIELECTRIC TFU-26GTC-VP-R
4C190 DC SP ANTENNA (KUVN CH 33 & KSTR CH 34)
AND ONE (1) DIELECTRIC TUM-AP-C4-14/48H-2-R-B
(KDTN CH 29)
LENGTH = 105.7 FT. OVERALL

DESIGN TOP ANTENNA PLATFORM ASSEMBLY FOR
MAXIMUM ALLOWABLE CAPACITY OF ANTENNA
LOADS AND FINAL BOLT PATTERN FROM ANTENNA
MANUFACTURER. TIGHTEN ALL FLANGE BOLTS USING
- "TURN OF THE NUT METHOD.

ANTENNA BASE REACTIONS:

MAXIMUM FACTORED WIND SHEAR: 9.8 KIPS
MAXIMUM FACTORED MOMENT: 453 KIP-FT
MAXIMUM FACTORED WEIGHT: 37 KIPS

ELEV. 1494.0' FROM T.O.C. TO TOP OF ANTENNA PLATE

STRUCTURAL FRAME ASSEMBLY

Dimensions:

- Vertical height: 10'-0" c-c
- Horizontal bays: 4'-3 1/2" +/-, 4'-8", 6'-0", 1'-6"
- Total height: 1475.5' from T.O.C.

Materials and Connections:

- Vertical Members:** C10 x 20# (A572 Gr.50) CHANNEL, PL 1 1/2" (A36) vertical leg flanges, 3 1/4" dia. bolts (A325X) typ.
- Horizontal Members:** T 4" x 3" x 5/16" (A36) diagonals, T 4" x 3" x 5/16" (A36) horizontals, T 3" x 2 1/2" x 1/4" (A36) horizontals, T 3" x 2 1/2" x 1/4" (A36) diagonals.
- Spacers and Bolts:** 5/8" dia. stitch bolt (A325X) with 1/2" thick spacer (A36) typ., 3/4" dia. bolts (A325X) typ., 5/8" dia. stitch bolt (A325X) with 1/2" thick spacer (A36) typ., 3/4" dia. bolts (A325X) typ., 3/4" dia. bolts (A325X) typ., 3/4" dia. bolts (A325X) typ.
- Design Notes:** GUSSETS SHALL DEVELOP MAXIMUM ALLOWABLE CAPACITY OF THE MEMBERS THAT ARE CONNECTED TO THEM - TYP.
- Vertical Leg:** 3 1/2" dia. solid (A572 Grade 50) vertical leg typ.
- Design End Connections:** DESIGN END CONNECTIONS TO DEVELOP DESIGN STRENGTH OF THE MEMBER PER ANSI/TIA 222-G TYP.
- Tension Rods:** TENSION RODS 7/8" dia. solid (A572 Grade 50)
- Elevation:** ELEV. 1475.5' FROM T.O.C.
- Notes:** SEE PAGE D05.07 FOR TOWER SECTION BELOW ELEV. 1475.5'.

SEE PAGE D05.07
FOR TOWER SECTION
BELOW ELEV. 1475.5'

ELEVATION VIEW



A BUSINESS OF FCI VENDÔTEL

200 North Water Street, Suite 215
King of Prussia, PA 19406

TOP OF TOWER DETAILS

DALLAS, TX

卷之三十一

THIS DRAWING IS THE PROPERTY OF STAINLESS AND TRANSFER CO., INC. IT IS TO BE KEPT CONFIDENTIAL, AND THE REPRODUCTION, USE OR DISCLOSURE, IN


REPRODUCTION OR USE OF THE DESIGN AND DETAILS CONTAINED HEREIN IS PROHIBITED
WITHOUT THE PRIOR WRITTEN PERMISSION OF THE APPLICANT.

www.ijerpi.org | ISSN: 2227-4321 | DOI: 10.18488/ijerpi.2020.10100


IN CHARGE	*	*	*	*	*	*	*	PREPARED BY	RE	28/08
	*							CHECKED BY	BT	29/08
	*							ENGINEER REVIEW	PEC	29/08/18
	*							PROJECT NUMBER		278349
	*									
	*									
	*							DRAWING NUMBER		D05.08
REV	BY	DATE	REVISION DESCRIPTION			D.CK	DATE	E.CK	DATE	
K:\278349\dwg\278349_D05.07_D05.08_Tower_Top.dwg										

NOTES:

1. PREP WELD AREAS - AREAS TO BE WELDED ARE TO BE FREE OF SCALE, RUST, GALVANIZING, AND SLAG. ALL BASE METALS SHALL BE PREPARED IN ACCORDANCE TO AWS D1.1.
2. REMOVE ANY GALVANIZING FINISH COMPLETELY WITHIN A 2" PERIMETER OF ANY WELD ZONES.
3. PREHEAT FLANGE AND LEG MATERIAL TO 250° F MINIMUM. MATERIAL SHOULD BE HEAT SOAKED THROUGH OR A 2" MINIMUM IN EVERY DIRECTION. NEW STIFFENER PLATES DO NOT REQUIRE PREHEAT.
4. USE LOW HYDROGEN WELD MATERIAL E70XX.
5. MAINTAIN 250° F MIN. DURING WELDING.
6. REFER TO AWS D1.1 FOR GENERAL WORKMANSHIP AND TECHNIQUE.
7. NO STARTS OR STOPS ARE ALLOWED AT THE END OF THE STIFFENER CORNERS. WELD WRAPS MUST BEGIN AND END AT 1" MIN. AWAY FROM THE CORNERS.
8. REFER TO ASTM A708 STANDARD PRACTICE FOR REPAIR OF A705-DIP GALVANIZED COATINGS.





SECTION VIEW 'A'-*A'*
TYPICAL FOR ALL (3) FLANGES
(TOWER MEMBERS NOT SHOWN FOR CLARITY)




FLANGE ELEVATION VIEW
TYPICAL FOR ALL (3) FLANGES

STAINLESS 		PREPARED BY		RE	20151
		CHICAGO	BY	2/15/14	
		THORNTON		BY	2/15/14
		PROJECT		NUMBER	278349
		DISHAWNO		DATE	D05.09
		ITEM/DESCRIPTION		REMARKS/NOTES	
FLANGE REINFORCEMENT DETAILS		RE BY DATE		REMARKS/NOTES	
DALLAS, TX					







A BUSINESS OF FDII VEHICLES
300 North Warner Road, Suite 215
King of Prussia, PA 19406




ARRANGEMENT FOR 7-3/16" R
DALLAS, TX

THIS DRAWING IS THE PROPERTY OF STAINLESS AND TRANSMITTED IN CONFIDENCE, AND THE REPRODUCTION, USE OR DISCLOSURE, IN WHOLE OR IN PART, OF THE DESIGN AND DETAILS CONTAINED HEREIN IS PROHIBITED.

 ALAN AHKUM PANG PROFESSIONAL ENGINEER 121108 PERMISSIONED	 STAINLESS <small>A BUSINESS OF FDH VEHICLEST</small> <small>200 North Warner Road, Suite 215</small> <small>Plano, Texas 75021</small>							PREPARED BY	RE	1/30/18			
								CHECKED BY	GT	2/19/18			
								ENGINEER REVIEW	PEC	2/04/18			
								PROJECT NUMBER	278349				
								DRAWING NUMBER	D06.02				
								REV. BY	DATE	REVISION DESCRIPTION	E.CK	DATE	E.CK
COAX ARRANGEMENT FOR 7-3/16" RIGID LINE													
DALLAS, TX													
<small>THIS DRAWING IS THE PROPERTY OF STAINLESS AND IS TRANSMITTED IN CONFIDENCE. THE REPRODUCTION, USE OR DISCLOSURE, IN WHOLE OR IN PART, OF THE DESIGN AND DETAILS CONTAINED HEREIN IS PROHIBITED WITHOUT THE PRIOR WRITTEN PERMISSION OF STAINLESS.</small>													
KA278349\dwg\278349_D06.00_Coax_Arrangement.dwg													

NOTES:

1. CONTRACTOR IS RESPONSIBLE TO ENSURE FIT UP TO EXISTING GUY ANCHOR AND TOWER END CONNECTIONS.
2. (3) GUY WIRE ASSEMBLIES REQUIRED FOR GUY LEVEL 4.
3. SEE PAGE D08.01 FOR TENSIONS AND INTERCEPTS.



PREPARED BY	REF	020715
CHIEFED BY	GT	211/16
ENGINEERED BY	PC	27-5-16
REVIEWED BY		
PRODUCT		
QUAIDER		
DRAWING		
NUMBER		
DATE		

STAINLESS

A Division of *Structural*
Engineering, Inc.

1000 Main Street, Suite 1000
Dallas, TX 75201-3100

GUY WIRE ATTACHMENT DETAILS

DALLAS, TX

3/1/18

THE ENGINEER AND ARCHITECT HAVE INSPECTED THE PLATES AND SPACERS AND DETERMINED THAT THEY ARE PROPERLY ATTACHED TO THE TOWER. THE CONTRACTOR IS RESPONSIBLE FOR THE ATTACHMENT OF THE GUY WIRE ASSEMBLIES.

3/1/18

THE STATE OF TEXAS
ALAN AH-KUM PANG
121108
LICENCED PROFESSIONAL ENGINEER

	0 DEG. F		20 DEG. F		40 DEG. F		60 DEG. F		80 DEG. F		100 DEG. F	
	ERECT. TENSION (LBS)	INTERCEPT (FT)										
1B	34460	14.3	32080	15.3	29783	16.5	27560	17.8	25479	19.3	23514	20.9
2B	35930	25.3	33734	26.9	31657	28.7	29700	30.5	27919	32.4	26262	34.4
3B	47063	27.4	45173	28.6	43350	29.8	41520	31.0	39805	32.4	38084	33.8
4B	45442	39.8	44126	40.9	42810	42.2	41520	43.4	40313	44.7	39065	46.1
5B	39506	124.4	38591	127.1	37699	129.9	36800	132.9	36050	135.4	35271	138.2
6B	43864	158.2	43156	160.9	42348	163.7	41500	166.8	40834	169.3	40103	172.1
7B	63114	198.9	62134	201.8	61191	204.6	60160	207.7	59415	210.1	58545	212.9
8B	40786	153.3	40189	155.6	39560	158.0	38880	160.8	38398	162.8	37832	165.2


ELEVATION VIEW - GUY #8

ELEVATION VIEW - GUY #1 THRU #7

PREPARED	RE	2011
CHICAGO	BY	1/9/13
ENGINER		1/22/13/13
INTERVIEW		
PROJECT NUMBER		278349
DRAWING NUMBER		D08.01
D.C.H. DATE: 1/23/13		
REVISION DESCRIPTION		
NOTES: 1. DURING THE INITIAL GUY TENSIONING PROCEDURES AND AT THE TIME OF INSPECTION, THE GUY TENSIONS AND/OR INTERCEPTS SHOULD BE IN ACCORDANCE WITH THE VALUES SHOWN ABOVE. USE THE TEMPERATURE WHICH ACTUALLY EXISTS AT THE TIME THE TENSION IS BEING CHECKED. FOR TEMPERATURES OTHER THAN THOSE SHOWN ABOVE, INTERPOLATE OR EXTRAPOLATE OTHER VALUES.		
2. TOWER PLUMBING AND INITIAL TENSIONING OF GUYS SHOULD BE DONE ONLY IN CALM WEATHER AND WITH NO ICE ON GUYS.		
3. USE INTERCEPTS AND TENSIONS IN GUY DIRECTION "B" ONLY.		
4. GUY #1 IS BOTTOM GUY; GUY #2 IS NEXT, ETC.		
5. USE SIGHT BAR FOR DETERMINING GUY INTERCEPTS.		
6. TENSION AND/OR INTERCEPT TOLERANCES +/- 5%.		
7. AFTER INSTALLING FINAL SET OF GUYS GO BACK AND RECHECK ALL LEVELS, RETENSIONING WHERE REQUIRED.		

STAINLESS
SHIPPING LIST AND BILL OF MATERIAL
DALLAS, TX

SHIP TO:			VIA:		SHIPPED BY:					
			JOB NO. 278349		DATE:					
			PACK	PPD	TRAILER NO:					
			SHIP	COL.	SHIPPING NO:					
SOURCE	QUAN	NAME	DESCRIPTION		WT.(lb)	MARK OR PART NO.				
	n/a		MATERIAL LIST FOR DRAWING D05.01		n/a					
	30	TENSION RODS	7/8" DIA. X 11'-8" LG. (APPROX.)		840					
	54	TENSION RODS	1" DIA. X 11'-8" LG. (APPROX.)		2106					
	36	TENSION RODS	1-1/4" DIA. X 11'-8" LG. (APPROX.)		2160					
	n/a		MATERIAL LIST FOR DRAWING D05.02		n/a					
	18	TENSION RODS	7/8" DIA. X 11'-8" LG. (APPROX.)		504					
	30	TENSION RODS	1" DIA. X 11'-8" LG. (APPROX.)		1170					
	36	TENSION RODS	1-1/4" DIA. X 11'-8" LG. (APPROX.)		2160					
	n/a		MATERIAL LIST FOR DRAWING D05.03		n/a					
	18	TENSION RODS	7/8" DIA. X 11'-8" LG. (APPROX.)		504					
	30	TENSION RODS	1" DIA. X 11'-8" LG. (APPROX.)		1170					
	42	TENSION RODS	1-1/4" DIA. X 11'-8" LG. (APPROX.)		2520					
	n/a		MATERIAL LIST FOR DRAWING D05.04		n/a					
	66	DIAGONAL ANGLES	L 3 X 2-1/2 X 1/4 X 12'-6" LG. (APPROX.)		3762					
	112	DIAGONAL ANGLES	L 3 X 2-1/2 X 1/4 X 6'-0" LG. (APPROX.)		3024					
	33	CENTER GUSSETS	PL 1/2" X 10" X 1'-8" LG. (APPROX.)		924					
	n/a		MATERIAL LIST FOR DRAWING D05.05		n/a					
	42	HORIZONTAL ANGLES	L 3 X 2-1/2 X 1/4 X 9'-3" LG. (APPROX.)		1764					
	n/a		MATERIAL LIST FOR DRAWING D05.06		n/a					
	48	SUB BRACE ANGLES	L 2-1/2 X 2-1/2 X 1/4 X 4'-3" LG. (APPROX.)		864					
	24	CENTER GUSSETS	PL 3/8" X 11" X 1'-4" LG. (APPROX.)		456					
	24	C-CLAMPS	PL 3/8" X 5" X 1'-3" (APPROX.)		192					
	24	C-CLAMP ASSEMBLIES	PL 3/8" X 5" X 1'-3" WELDMENT (APPROX.)		336					
	n/a		MATERIAL LIST FOR DRAWING D05.07, D05.08		n/a					
	3	LEG ASSEMBLIES	RB 3-1/2" DIA. X 19'-6" LG. WELDMENT		21450					
	12	TENSION RODS	7/8" DIA. X 11'-8" LG. (APPROX.)		336					
	12	DIAGONAL ANGLES	L 3 X 2-1/2 X 1/4 X 6'-10" LG. (APPROX.)		384					
	3	CENTER GUSSETS	PL 1/2" X 10" X 1'-2" LG. (APPROX.)		60					
	6	HORIZONTAL ANGLES	L 3 X 2-1/2 X 1/4 X 8'-3" LG. (APPROX.)		252					
	3	LEG ASSEMBLIES	RB 3-1/2" DIA. X 18'-6" LG. WELDMENT		20370					
	6	TENSION RODS	7/8" DIA. X 11'-8" LG. (APPROX.)		168					
	12	DIAGONAL ANGLES	L 3 X 2-1/2 X 1/4 X 5'-10" LG. (APPROX.)		324					
	3	CENTER GUSSETS	PL 1/2" X 10" X 1'-2" LG. (APPROX.)		60					
	12	DIAGONAL ANGLES	L 4 X 3 X 5/16 X 5'-3" LG. (APPROX.)		456					
	3	HORIZONTAL ANGLES	L 3 X 2-1/2 X 1/4 X 9'-3" LG. (APPROX.)		126					
	6	HORIZONTAL ANGLES	L 4 X 3 X 5/16 X 9'-3" LG. (APPROX.)		402					
	1	ANTENNA PLATFORM	C10 X 20# X 8'-3" LG. WELDMENT (APPROX.)		1200					
TOTAL WEIGHT THIS PAGE:				70044 lb	DESCRIPTION		REV	PREP BY:		
DRAFTING RELEASE:	CHECKED BY:		PACKED BY:	TOTAL WEIGHT THIS SHIPMENT:						
				70044 lb						





A BUSINESS OF 3000 INFRASTRUCTURE SERVICES

REPORT 278348

ATC Site: 75253 Milton/Cedar Hill


DATE: 12/05/2017

RIGOROUS STRUCTURAL ANALYSIS

FOR A 1455' STAINLESS G-10 GUYED TOWER

DALLAS, TEXAS

PREPARED BY: PCC/215-631-1326 APPROVED: AP
CHECKED BY: AP/215-631-1329



Date	Pages	Remarks
2/12/2018	7-9	Rev A: New soil data & updated Para. G2c
5/4/2018	10	Rev B: Revised Para. G4

Rev.	Date	Description
A	2/12/18	New soil data & updated Para. G2c
B	5/4/18	Revised Para. G4

<u>SECTION</u>	<u>PAGE</u>
A. AUTHORIZATION/PURPOSE	1
B. TOWER HISTORY	1
C. CONDITIONS INVESTIGATED	3
D. LOADS AND STRESSES	6
E. METHOD OF ANALYSIS	6
F. RESULTS	6
G. CONCLUSIONS AND RECOMMENDATIONS	8
H. PROVISIONS OF ANALYSIS	10

APPENDIX

GENERAL ARRANGEMENT	E-1
LINEAR APPURTENANCES	A-2

Rev.	Date	Description
A	2/12/18	New soil data & updated Para. G2c
B	5/4/18	Revised Para. G4

A. AUTHORIZATION/PURPOSE

As authorized by Geoffrey Middlebrooks of American Tower Corporation (ATC), a structural analysis was performed to investigate the adequacy of a 1455' Stainless G-10 guyed tower in Dallas, Texas to support specified equipment.

B. TOWER HISTORY

The tower was originally designed and furnished in 1980 by Stainless, Inc. It was designed in accordance with EIA Standard RS-222-C for a wind load of 51 psf, to support the following:

1. One (1) slotted tube array antenna (Channel 33), top-mounted and fed by one (1) 8-3/16" coax.
2. One (1) RCA TFU-36JDAS antenna (Channel 21), top-mounted and fed by one (1) 8-3/16" coax.
3. One (1) RCA TFU-36JDAS antenna (Channel 27), top-mounted and fed by one (1) 8-3/16" coax.
4. One (1) ERI panel type FM antenna directly below the top platform, fed by one (1) 6-1/8" coax.
5. One (1) V-Z antenna (Channel 16) below the ERI panel type FM antenna, fed by one (1) 8-3/16" coax.
6. Three (3) 8' wide, three-sided platforms to support 41 communication cabinets and 30 communications antennas, one (1) platform each at the 895', 1080' and 1270' levels.
7. Three (3) 2" conduits for three (3) power circuits, one (1) to each outside platform.
8. Three (3) 1-1/2" conduits for three (3) telephone cable circuits, one (1) to each outside platform.
9. One (1) two-person, double-deck elevator by Marshall Elevator Co., with control circuit.
10. One (1) 3" conduit for the lighting system and two (2) de-icers.
11. One (1) ladder to the top of the tower.
12. Two (2) 6' dishes at the first guy level, each fed by one (1) 1" line.
13. One (1) 8' x 12' reflector at the first guy level.
14. Two (2) 6' dishes at the second guy level, each fed by one (1) 1" line.
15. One (1) 8' x 12' reflector at the second guy level.
16. Two (2) 6' dishes at the third guy level, each fed by one (1) 1" line.
17. One (1) 8' x 12' reflector at the third guy level.

The tower has been modified since the original erection in 1980. The modifications are as follows:

1986 - Modification under Stainless, Inc. Contract 2783-7
Replaced guy wires at levels 2 and 4 and re-tensioned guys.
Installed ten (10) bays of leg sub-bracing.

Rev.	Date	Description
A	2/12/18	New soil data & updated Para. G2c
B	5/4/18	Revised Para. G4

Replaced thirteen (13) bays of diagonal braces.

1988 - Modification under Stainless, Inc. Contract 278311
Replaced three (3) levels of horizontal braces.
Replaced eight (8) bays of diagonal braces.

1989 - Modifications under Stainless, Inc. Contract 278315
Replaced two (2) levels of horizontal braces.
Replaced ten (10) bays of diagonal braces.

1990 - Modifications by others.
Replaced four (4) bays of diagonal braces.

1997 - Modifications under Stainless, Inc. Contract 278319
Replaced guy wire at level 2 and re-tensioned guys.

2002 - Modifications by Kline Iron & Steel Co., Inc.
Replaced guy wires at level 3 and re-tensioned guys.
Installed twenty-two (22) bays of leg sub-bracing.
Replaced fourteen (14) bays of diagonal braces.
Installed reinforcement to candelabra structure.

2005 - Modifications by Kline Iron & Steel Co., Inc.
Installed two (2) bays of leg sub-bracing.

2006 - Modifications under Stainless LLC. Contract 278330
Re-tensioned guys and replaced one (1) bay of diagonals.

2007 - Modifications under Stainless LLC. Contract 278332
Re-tensioned guys and replaced two (2) bays of diagonals.

2008 - Modifications under Stainless LLC. Contract 278335
Re-tensioned guys and replaced one (1) bay of diagonals.

2010 - Modifications by others. Re-tensioned the guys per the recommended tensions of
Stainless LLC Contract 278338.

2011 - Modifications under Stainless LLC. Contract 278342
Replaced two (2) bays of diagonals.

2014 - Modifications under Stainless LLC. Contract 278344
Replaced one (1) bay of diagonals.

Rev.	Date	Description
A	2/12/18	New soil data & updated Para. G2c
B	5/4/18	Revised Para. G4

C. CONDITIONS INVESTIGATED

The analysis was performed for the tower supporting equipment based upon the following sources:

- Stainless LLC Report 278345 dated 03/22/2017.
- Load List Milton-Cedar Hill 75253 103117-FINAL, provided by American Tower Corporation.
- All emails from Christina Minor and Geoffrey Middlebrooks of ATC dated between 11/02/2017 and 11/20/2017.
- An email from Christina Minor ATC dated 11/20/2017 with approved tower loading and tower cross section.

ITEM	APPURTENANCE	ELEVATION, ft.	FEED LINES
1	(1) ERI 1183-8CP-2 8-bay panel antenna	1380	(1) 6-1/8" rigid line and (1) 2-1/2" conduit
2	(1) ERI 1183-6CP-2 6-bay panel antenna	1303	(1) 5" Conduit (5.56" OD) and (1) 2-1/2" conduit
3	(1) MCI 952000 (6-bay with 2 panels each bay) antenna	1271	(1) 6-1/8" rigid line
4	(1) SWR 4-bays slot antenna side mount to tower leg	1156	(1) 4-1/16" rigid line
5	(1) Scala CL-46/HRM/50N Yagi antenna	1145	(1) 1-5/8"
6	(1) Scala CL-46/HRM/50N Yagi antenna	1133	Shares line with Yagi antenna at the 1145' level
7	(1) SBP UP8-C LPTV antenna	1095	(1) 4" line
8	(1) BSP UP8 C LPTV antenna	1072	(1) 3" line
9	(1) Dielectric THA-C2 antenna	1072	(1) 3" line
10	(1) ProScan III ENG antenna	995	(1) 1-1/4" line and (1) 7/8" line
11	(1) Micro Communication Ch30 and Ch 50 side mounted antenna	950	(1) 4" line
12	(1) Telewave ANT150F6-7 antenna on platform handrail mount	905.5	--

Rev.	Date	Description
A	2/12/18	New soil data & updated Para. G2c
B	5/4/18	Revised Para. G4

13	(2) 18"x12" junction box (1) 5412 ESS242010 unit (1) 24"x24"x14" junction box (1) 48"x24" junction box	899	(2) 3/8"cables
14	(1) DB420 MS-E dipole antenna	892.5	(1) 7/8" line
15	(1) 8' wide, three-sided platform	892	(1) 2" and (1) 1-1/2" conduit
16	(1) MCI 955138 antennas (8-bay each bay with 2 panels)	840	(1) 4" line and (1) future 4" line
17	(1) MCI 952000-4 antennas (4-bay each bay with 2 panels)	793	(1) 3" line
18	(1) ERI SHPX-8AC6-HW FM antenna	745	(1) 3-1/8" line
19	(6) AN1430-01 antennas and (24) BMAX-BST-AU-ODU units	658	(24) 5/8" lines
20	(1) MCI 955138 antenna (8-bay each bay with 2 panels)	591	(1) 3" line
21	(1) 4' Yagi antenna	577.5	(1) 7/8" line
22	(1) DB420MS-E dipole antenna	569.5	(1) 7/8" line
23	(1) 10' grid dish antenna	528	(1) 7/8" line
24	(1) DB224-E dipole antenna; (1) 20' dipole antenna; and (1) 10' grid dish antenna	500	(1) 7/8" line and (1) 1-1/4" line
25	(1) 12' ice shield	410	
26	(1) 3' Yagi antenna	405	(1) 7/8" line
27	(1) 12' standard dish antenna	400	(1) 7/8" line
28	(1) 6' ice shield	387	
29	(1) 10'grid dish antenna	382	(1) 7/8" line
30	(1) 8'grid dish antenna	378	(1) 7/8" line
31	(1) 6'standard dish antenna and (1) 10' grid antenna	362	(2) 7/8" line
32	(1) RFS PD200 omni antenna	360	(1) 7/8" line
33	(1) 8' HP dish antenna	352.5	(1) EW63 cable
34	(1) 2' grid dish antenna	334	(1) 1-5/8" line
35	(1) 10' grid dish antenna	333	(1) 1-5/8" line
36	(2) 8' standard dish antennas	330	(2) 1/2" lines
37	(1) 10' grid dish antenna	326	(1) 7/8" line
38	(1) RFS DA12-65AC dish antenna	325	(1) EW63 cable
39	(1) 12' ice shield	306	
40	(1) 8' standard dish antenna	300	n/a
41	(1) UHX6-59-P3A/L HP dish antenna	300	(1) EW63 cable
42	(1) RFS DA12-65AC dish antenna	275	(1) EW63 cable

Rev.	Date	Description
A	2/12/18	New soil data & updated Para. G2c
B	5/4/18	Revised Para. G4

43	(2) 6' ice shields	267	
44	(2) RFS SBX2-107NEC HP dishes	262	(4) 3/8" lines
45	(3) CSS X7C-665 and (3) Jaybeam PCSX065-18-0 antennas; (3) LGP18601 TTA units on sector frames	252	(9) 1-5/8" lines
46	(1) 3' standard dish antenna	224	(1) 0.19" line
47	(1) 12' ice shield	212.5	
48	(1) 12' grid dish antenna	203	(1) 7/8" line
49	(1) Scala CA7-410 Yagi antenna	200	(1) 7/8" line
50	(1) PL8-65 8' standard MW dish antenna	200	(1) EW63 cable
51	(1) 6' standard dish antenna	190	(1) 1/2" line
52	(1) 8' grid dish antenna	188	(1) 7/8" line
53	(1) 10' grid dish antenna	170	(1) 7/8" line
54	(1) 2' Yagi antenna	153	(1) 1/2" line
55	(1) 4' standard dish antenna and (2) TTA units	131	(1) 1-5/8" line
56	(1) 2' Yagi antenna	107	(1) 3/8" line
57	(1) 4' standard dish antenna	105	(1) 1-5/8" line
58	(1) 10' omni antenna	70	(1) 7/8" line
59	(1) conduit	To 1443	(1) 1-1/4" conduit
60	(1) line support conduit (assumed)	To 1072	(1) 1-1/2" conduit
61	(1) line support conduit (assumed)	To 950	(1) 1-1/2" conduit
62	(1) line support conduit (assumed)	To 500	(1) 3/4" conduit
63	(1) line support conduit	To 252	(1) 1-1/2" conduit
64	(1) line support conduit	To 610	(1) 1-1/4" conduit
65	(1) line support conduit (assumed)	To 325	(1) 1-1/2" conduit
66	(1) two man, double-deck elevator	1455	(1) 3/4" conduit containing control circuits
67	(1) lighting system	Tower top	3" conduit
68	(1) climbing ladder without safety cable	Tower top	--
	*** Proposed Loading***		
69	(1) TFU-26GTC-VP-R 4C190 DC SP / (1) TUM-AP-C4- 14/48H-2-R-B stack antenna system on top of a new 39-ft tower mast extension on top of main tower	Tower Top	(1) 8-3/16" rigid line; (2) 7-3/16" rigid lines

Rev.	Date	Description
A	2/12/18	New soil data & updated Para. G2c
B	5/4/18	Revised Para. G4

Locations of transmission lines are based upon Stainless Report 278345 dated 03/22/2017. The transmission line arrangement is summarized on page A-2 of this report. Deviating from this arrangement will affect the accuracy of this analysis.

All existing antennas, antenna mounting pedestals on top candelabra and antenna feed lines will be removed and will not be included in this analysis. The modifications of Report 278345 have not been installed.

D. LOADS AND STRESSES

The analysis was performed using the following design parameters in accordance with 2015 IBC and ANSI/TIA 222-G-2005, Structural Standard for Antenna Supporting Structures and Antennas, including addenda 1 & 2, dated 2007 and 2009 respectively.

- Risk Category II
- 115 mph ultimate design wind speed with no ice.
- 30 mph nominal design wind speed with 3/4" design ice thickness
- Exposure Category D
- Topographic Category 1
- 0.11 earthquake spectral response acceleration at short periods (S_s)
- Earthquake Site Class D

Seismic effects need not be considered as the value of S_s is less than 1.0 per Section 2.7.3 of ANSI/TIA 222-G. Load and resistance factors used to evaluate the adequacy of the structure were in accordance with ANSI/TIA 222-G.

E. METHOD OF ANALYSIS

The analysis was performed using tnxtower and RISA3D, computer-aided finite element programs for analysis of structures and towers subject to simultaneous transverse and axial loads.

F. RESULTS

The results of the analysis show the following ratings:

LOCATION	SPAN	RATING %
Candelabra	Chords	34
	Vertical bracing	52
	Horizontal bracing	58
	Diagonal bracing	95
	Pedestal members	42
	Knee bracing	46
Leg Compression	8	137
	7	183
	6	156
	5	97

Rev.	Date	Description
A	2/12/18	New soil data & updated Para. G2c
B	5/4/18	Revised Para. G4

Leg Tension	4	113
	3	89
	2	91
	1	87
	8	42
	7	--
	6	--
	5	--
	4	--
	3	--
Diagonals	2	--
	1	--
	8	109
	7	94
	6	134
	5	217
	4	176
	3	146
Horizontals	2	211
	1	184
	8	113
	7	84
	6	117
	5	167
	4	160
	3	134
Guys	2	190
	1	150
	8	86
	7	70
	6	66
	5	82
	4	106
	3	100
Foundations	2	111
	1	91
	Base	110
Inner anchors		84
Outer anchors		83

The rating is defined as the percentage of the component design capacity that is used up in supporting itself and the loading from the antennas and transmission lines under the design wind

Rev.	Date	Description
A	2/12/18	New soil data & updated Para. G2c
B	5/4/18	Revised Para. G4

and ice loading conditions. Ratings of up to 105% are considered acceptable due to tolerances in calculating the applied loads on the tower as well as component design capacities.

With new soil parameters for inner guy anchors provided by FDH Velocitel, Project number: 18PAMC1401, dated 02/01/2018, the inner guy anchors new ratings are 84% and inner anchors are adequate.

G. CONCLUSIONS AND RECOMMENDATIONS

Based on the preceding results, the following conclusions may be drawn:

1. The tower, supporting the equipment as specified in section C of this report, is not adequate to achieve an ultimate wind speed of 115 mph with no ice and 30 mph nominal wind speed with 3/4" design ice thickness in accordance with the 2015 IBC and ANSI/TIA 222-G with the parameters.
2. In order to achieve an ultimate wind speed of 115 mph with no ice and 30 mph nominal wind speed with 3/4" design ice thickness in accordance with the 2015 IBC, and ANSI/TIA 222-G with the analysis parameters of Section D, the following modifications are required:
 - a. Replace guy level 4 guy wires with new, higher strength guy wires.
 - b. Adjust guy wire initial tensions for all guy levels.
 - c. [Deleted; inner anchors adequate after review with new geotechnical report]
 - d. Install additional horizontal sub-bracing members at the midpoints of the following bays:

Location	No. of bays
1153.8' – 1108.8'	6
1093.8' – 1086.3'	1
1071.3' – 1063.8'	1

- e. Replace existing diagonal members with new, higher capacity members at the following bays:

Location	No. of bays
1033.8' – 1011.3'	3
853.8' – 838.8'	2
823.8' – 808.8'	2
778.8' – 718.8'	8
696.3' – 658.8'	5
621.3' – 613.8'	1
606.3' – 576.3'	4
553.8' – 531.3'	3
463.8' – 441.3'	3
396.3' – 388.8'	1
381.3' – 366.3'	2

Rev.	Date	Description
A	2/12/18	New soil data & updated Para. G2c
B	5/4/18	Revised Para. G4

343.8' – 246.3'	13
238.8' – 216.3'	3
208.8' – 178.8'	4
156.3' – 141.3'	2
133.8' – 73.8'	8

f. Replace existing horizontal members with new, higher capacity members at the following levels:

Location	No. of levels
1041.3' – 1033.8'	2
208.8' – 201.3'	2
133.8' – 118.8'	3

g. Reinforce tower top existing leg flanges in order to have adequate strength for additional new 39-ft tower mast on top of existing main tower.

3. After the above modifications are completed, the twist and sway at the elevation of the dish at the service wind speed of 60 mph are as follows:

Dish	Elevation, ft.	Twist, degrees	Sway, degrees
10' grid dish	528	1.26	0.15
10' grid dish	500	1.23	0.12
12' standard dish	400	1.16	0.10
10' grid dish	382	1.15	0.10
8' grid dish	378	1.15	0.10
6' standard dish	362	1.15	0.10
8' HP dish antenna	352	1.15	0.10
2' dish	334	1.16	0.10
10' grid dish	333	1.16	0.10
8' standard dish	330	1.16	0.10
10' grid dish	326	1.16	0.10
RFS DA12-65AC dish	325	1.16	0.10
8' standard dish	300	1.17	0.11
UHX6-59-P3A/L HP dish	300	1.17	0.11
RFS DA12-65AC dish	275	1.15	0.12
(2) RFS SBX2-107NEC HP dishes	262	1.12	0.13
3' standard dish	224	0.96	0.16
12' grid dish	203	0.87	0.16
PL8-65 dish	200	0.86	0.17
6' standard dish	190	0.83	0.17
8' grid dish	188	0.82	0.18

Rev.	Date	Description
A	2/12/18	New soil data & updated Para. G2c
B	5/4/18	Revised Para. G4

10' grid	170	0.75	0.18
4' standard dish	131	0.55	0.19
4' standard dish	105	0.41	0.20

4. The following table shows a comparison between the current loads and the design resistance of the tower base.

Component	Design resistance x 105% (kips)	Current load (kips)	Factor of safety	Status
Download	3712	3899	1.91	Acceptable

H. PROVISIONS OF ANALYSIS

The analysis performed and the conclusions contained herein are based on the assumption that the tower has been properly installed and maintained, including, but not limited to the following:

1. Proper alignment and plumbness.
2. Correct guy tensions.
2. Correct bolt tightness.
3. No significant deterioration or damage to any component.


Furthermore, the information and conclusions contained in this Report were determined by application of the current "state-of-the-arts" engineering and analysis procedures and formulae, and Stainless assumes no obligations to revise any of the information or conclusions contained in this Report in the event that such engineering and analysis procedures and formulae are hereafter modified or revised. In addition, under no circumstances will Stainless have any obligation or responsibility whatsoever for or on account of consequential or incidental damages sustained by any person, firm or organization as a result of any information or conclusions contained in the Report, and the maximum liability of Stainless, if any, pursuant to this Report shall be limited to the total funds actually received by Stainless for preparation of this Report.

Customer has requested Stainless to prepare and submit to Customer an engineering analysis with respect to the Subject Tower and has further requested Stainless to make appropriate recommendations regarding suggested structural modifications and changes to the Subject Tower. In making such request of Stainless, Customer has informed Stainless that Customer will make a determination as to whether or not to implement any of the changes or modifications which may be suggested by Stainless and that Customer will have any such changes or modifications made by riggers, erectors and other subcontractors of Customer's choice.

Customer hereby agrees and acknowledges that Stainless shall have no liability whatsoever to Customer or to others for any work or services performed by any persons other than Stainless in connection with the implementation of any structural changes or modifications recommended by Stainless including but not limited to any services rendered for Customer or for others by riggers,

Rev.	Date	Description
A	2/12/18	New soil data & updated Para. G2c
B	5/4/18	Revised Para. G4

erectors or other subcontractors. Customer acknowledges and agrees that any riggers, erectors or subcontractors retained or employed by Customer shall be solely responsible to Customer and to others for the quality of work performed by them and that Stainless shall have no liability or responsibility whatsoever as a result of any negligence or breach of contract by any such rigger, erector or subcontractor.




ALL REACTIONS ARE FACTORED



Stainless
200 N Warner Road, Suite 215
King of Prussia, PA 19406
Phone: 6109924101
FAX: 6109924109

Job:	Report 278348; Dallas, TX; Result Run		
Project:	1455-ft Stainless G-10 Candelabra Guyed Tower		
Client:	American Tower Corporation	Drawn by:	C.Chen
Code:	TIA-222-G	Date:	12/05/17
Path:	K:\278348\eng1\NXTower\278348_Result_Run.rer		
			Dwg No. E-1



STAINLESS		REVISION DESCRIPTION			PREPARED BY	PCC	11/17/2017
A Division of FOM VEHICLES 100 West Main Street, Suite 400 Langdale, PA 16446		REV	BY	DATE	DATE	E.CK	DATE
LINEAR APPURTENANCES DALLAS, TX							

THIS DRAWING IS THE PROPERTY OF STAINLESS AND IS TRANSMITTED IN CONFIDENCE AND THE REPRODUCTION, USE OR DISCLOSURE, IN WHOLE OR IN PART, OF THE DESIGN AND DETAILS CONTAINED HEREIN IS PROHIBITED WITHOUT THE PRIOR WRITTEN PERMISSION OF STAINLESS.

ATC TOWER INSPECTION FORM



ANSI-TIA/EIA-222 Compliant

Page 1

SECTION A - SITE INFORMATION

ATC Site Number	: 75253	ATC Site Name, State	: CEDAR HILL - MILTON, TX
Site Address	: 1360 W. Belt Line Rd.	Number of Compounds	: 1
City/State	: Cedar Hill, TX	Date of Inspection	: 6/20/16
Contractor Name	: Structural Components		
Inspection Completed By	: Chance Adams, David Begley, Wes Culver		

SECTION B - TOWER INFORMATION

Structure Type	: Guyed	Number of Tower Legs	: 3
Tower Height	: 1455.0	Climbing/Safety Device	: No
Overall Structure Height	: 1529.5	FCC/ASR Number	: 1055009
Tower Manufacturer	: Unknown	AM Detuning ?	: No

SECTION C - SITE INFORMATION CATEGORIES

SECTION A - Site Information	SECTION I - AM Detuning Comments
SECTION B - Tower Information	SECTION J - Dampers Comments
SECTION C - Tower Information Summary Comments	SECTION K - Lights Comments
SECTION D - Tower Foundation Comments	SECTION L - Elevator Comments
SECTION E - Tower Structure Comments	SECTION M - Transmission Line Bridges Comments
SECTION F - Safety Comments	SECTION N - RF Equipment Comments
SECTION G - Grounding Comments	SECTION O - Compliance
SECTION H - Guy Anchors & Wires Comments	

SECTION D - TOWER FOUNDATION

Instructions

Tower base should be visually inspected for spalling and cracking of the concrete. The soil surrounding the tower base foundation should be inspected for evidence of settlement. Any such settlement or movement should be noted.

Base drains (if present) should be clear of any obstructions. Penetrate drain with object to ensure drains functioning.

Base Insulators (if present) - The porcelain surface should be wiped clean with a soft cloth to remove any salt deposits or other foreign substance. A check should be made for any evidence of deterioration or cracks in the porcelain surface.

All discrepancies must be marked with masking tape and magic marker.

All discrepancies must be noted and photographed and numbered.

Yes	No	Corrected	N/A
X			
X			
X			
			X
X			

Place an x in the proper box

If any comments exceed one row
please expand the row height so that
all of the text is visible. To expand
rows automatically, click the Select
All button, then click AutoFit Row
Height in the Cells/Format box

Is tower center pin in place?

Is tower center pin free of corrosion?

Are all base plate bolts, nuts, and washers present?

Is the tower foundation in good condition? (No cracking, spalling, or settling)

Is the concrete lower base free from standing water?

Are base drains clear and free flowing? (Drains required only under tubular legs.)

Is porcelain surface of base insulators in good condition? (No deterioration or cracking)

Is the soil around the foundation in good condition? (No settling or movement)

Comments:

1. Light rust on baseplate stack. (Photos 86, 87)

2.

3.

4.

RECEIVED

APR 4 2018

CITY OF CEDAR HILL
PLANNING

RECEIVED

APR 4

CITY OF CED.
PLANNING

Instructions

Corrosion - If corrosion is observed, the source should be determined and noted.

Damaged or faulty members - A visual inspection must be made of the entire tower structure to determine if any of the members have been deformed or damaged. Any bowed, bent or damaged member/bolt should be noted as to part number, size, location on tower, nature and magnitude of deformation or damage.

Do not remove any tower member for replacement unless authorized by ATC Engineering Dept - Signed/Sealed Construction Drawings are required if a

All discrepancies must be marked with masking tape and magic marker. All discrepancies must be noted and photographed before and after repair.

Are all bolts and nuts tight? Tighten loose bracing bolts and document as corrected. Loose

Is the tower free of rust? (If "No", be specific in the comments below.)

Are all structural members straight and not damaged, bent, and/or missing?

Is the tower finish in good condition? (No obvious signs of cracking)

Is the weld free of rust and not damaged? (If "No", be specific in the below)

Yes	No	Corrected	N/A
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Place an x in the proper box

Comments:

1. Light rust and chipped paint typical in many places throughout tower members and bolts. Esp in white areas. (Photos 484, 487, 571, 589, 620)
2. Rusty hardware in several places on tower including climbing ladder, coax hangers, trap door chains, antenna mounts (Photos 423, 446, 448, 553, 629)
3. Unused ice shields on tower, see line and antenna report (Photo 300)
4. Unused conduits on tower (Photo 678)
5. Unused equipment on tower, see line and antenna report (Photo 135)
6. Active small-bird nest, C-Leg 165' (Photo 566)
7. Moderate rust on antenna mount C-Leg Dish @ 131' (Photo 553)
8. Overgrown base compound (Photo 51-54)
9. Compound fence is rusted and barbed wire is loose (Photo 46, 75)

SECTION F - SAFETY**Instructions**

Safety is paramount- Report anything that makes it unsafe to operate or maintain this tower to ATC immediately.

All discrepancies must be marked with masking tape and magic marker. All discrepancies must be noted and photographed before and after repair.

Is there a safety climb system?

Are all components of the safety climb system free of rust?

Is the cable free from kinks, fraying, broken wires or strands or other damage?

Is the climbing path free from obstructions allowing a clear path for the cable?

Is the cable secured by properly spaced cable guides?

Is the total system properly installed including the top connection? If No, correct and note.

Is the FCC and ATC signage apparent and placed properly.

Is the ladder continuous, if "No", be specific in the comments

Are the platforms secured with proper handrails and/or anchorages

Yes	No	Corrected	N/A
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Place an x in the proper box

Comments:

1. No safety cable system installed on tower. (Photo 395)
- 2.
- 3.
- 4.

SECTION G - GROUNDING**Instructions**

Connections - The connections above grade should be visually checked for loose fittings, ensure wires are snug in mechanical connections or well bonded with exothermic connections at the base of the tower.

Ground Wires - The ground wires at the base should be cad welded to each leg.

Take a photo of the grounding at the base and at each anchor.

All discrepancies must be marked with masking tape and magic marker. All discrepancies must be noted and photographed before and after repair.

Is the lower base properly grounded?

Are the guy cables and/or guy anchor heads properly grounded?

Are ground wires and connections in satisfactory condition?

Is there a lightning rod or static dissipation array installed on this tower?

Is lightning rod or static dissipation array properly installed, if present?

Is the lightning rod mounted in a location making it the highest point on the tower?

Yes	No	Corrected	N/A
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Place an x in the proper box

Comments:

1. No grounding on wires or fanplate: Bi, Bo, Co. (Photos 184, 190, 196, 227)
2. Frayed grounding on Ci (Photo 223)
3. No fanplate grounding: Ai, Ao, Ci. (Photos 155, 177, 213)
4. Guy wire ground clips rusted: Ai, Ao, Bi, Bo, Ci. (Photos 160, 171, 198, 214)
5. One ground at base is disconnected, there are still (3) connected grounds though (Photo 83)
- 6.
- 7.
- 8.
- 9.
- 10.

Instructions

All discrepancies must be marked with masking tape and magic marker. All discrepancies must be noted and photographed before and after repair.

Yes	No	Corrected	N/A

Place an x in the proper box

Are all lights properly operational in both day and night mods?

Is there any light outage?

Are connection in good condition for resistance to entry of water?

Are drain and openings unobstructed?

Are junction boxes and wiring in good condition?

Do light lenses have cracks and crazing?

Comments:

1. Small lights behind Face FM antennas may be considered obstructed (Photo 450)

2.

3.

4.

5.

SECTION L - Elevator**Instructions**

All discrepancies must be marked with masking tape and magic marker. All discrepancies must be noted and photographed before and after repair.

Yes	No	Corrected	N/A

Place an x in the proper box

Does elevator travel full range?

Do upper and lower limit switches work properly?

Are cables in good condition (corrosion, birdcaging, broken wires in strand)

Do emergency breaks work properly?

Are elevator sheaves in good condition?

Are machine fluid at proper levels?

Comments:

1. Cab controls were not working at time of inspection. Elevator could be operated from ground but only by manually holding down contact switches.
2. Emergency breaks were not tested at time of inspection. Top limit switch was not tested.
3. Light corrosion of wires, rails, top wheels and other hardware (Photos 403, 423, 446)
4. Moderate rust on elevator stop brackets (Photo 443, 444)
5. Elevator sheaves have light rust (Photo 386)
6. Emergency breaks were not tested at time of inspection. Top limit switch was not tested.

SECTION M - Transmission Line Bridges**Instructions**

All discrepancies must be marked with masking tape and magic marker. All discrepancies must be noted and photographed before and after repair.

Yes	No	Corrected	N/A

Place an x in the proper box

Are all bolts and nuts tight? Tighten loose bracing bolts and document as corrected. Loose

Is the tower free of rust? (If "No", be specific in the comments below.)

Are all structural members straight and not damaged, bent, and/or missing?

Is the tower finish in good condition? (No obvious signs of cracking)

Comments:

1. Moderate surface rust on transmission line bridge from "Building 2" (Photo 115, 116)
- 2.
- 3.
- 4.
- 5.

SECTION M - RF Equipment**Instructions**

All discrepancies must be marked with masking tape and magic marker. All discrepancies must be noted and photographed before and after repair.

Yes	No	Corrected	N/A

Place an x in the proper box

Is mounting support in good condition? (Including any ice shields)

Are line support hangers in good condition? (Type, quantity, and spacing)

Is antenna in good condition?

Is feed line in good condition?

Comments:

1. Cracked antenna shrouds: Top face FM bottom bay, TV @ 1125' top bay shroud, Superquad shroud @ 1023'. (Photos 606, 642, 649)
2. Unstable ice shield, C-Leg, 210'. Seems insufficiently braced- based on how easily it moves. Could really move in wind. (Photo 706, 707)
3. Unattached coax at 260', and a few other spots. (Photo 709)
4. Moderate rust on top hangers for copper lines and Face mount FM line support (Photo 440, 448, 449)
5. Light rust on copper lines from building to tower. (Photo 126)

SECTION O - COMPLIANCE

I understand that this information and form are the sole property of American Tower Corporation
and may not be copied or shared without written permission from ATC.
I certify this report to be accurate and complete to the best of my knowledge and belief.

Name : Chance Adams

Date : 6/20/16

Company : Structural Components, LLC



Copyright © ATC IP, LLC - All Rights Reserved

ATC TOWER MAPPING

3500 Regency Pkwy, Ste 100
Cary, NC 27518
Phone: 919-468-0112
www.americantower.com

TOWER MAPPING REPORT

75253 - MILTON/CEDAR HILL
1360 W. Belt Line Rd., Cedar Hill, TX
1455ft Guyed Tower

Contractor report # 160443
Date: 07-05-2016



RECEIVED

Prepared By:




APR 4 2018

CITY OF CEDAR HILL
PLANNING

Information Notes:

- Include names of all crew members present at site.
- Contact to be person to whom any questions regarding this mapping should be directed.
- Crew leader signature indicates that tower mapping is complete and accurate per company and ATC standards.

CONTRACTOR INFORMATION AND SIGNATURE	
Company Name	Structural Components, LLC
Company Address	11611 E. 51st Ave, Denver, CO 80239
Contact Person / Phone #	Wes Culver / 303-435-4647
Project Manager	Wes Culver
Tower Mapping Date	June 20th - 21st, 2016
Crew Members	Wes Culver, Chance Adams, David Begley
CAD Initials	WC
Report Number	160443
Report Completion Date	07/05/16
Crew Leader Signature	

Information Notes:

- Initial each item when completed and identify the correct page number(s).
- Add or remove items / lines as necessary based on tower.
- Use notes column to identify any issues or further information.

Information Notes:

- Add notes to identify problem areas that were identified and corrected.
- Use notes to list and explain exception to standard procedures.

SITE INFORMATION	
Site Name	MILTON/CEDAR HILL
Site Number	75253
Site Address	1360 W. Belt Line Rd., Cedar Hill, TX 75104
County	Dallas
Latitude	32.58945
Longitude	-96.97025
Driving Instructions	From Dallas/Fort Worth International Airport: Take State Hwy 161 S/TX-161 S and President George Bush Turnpike S to FM1382 S/Belt Line Rd in Grand Prairie. Take exit 457 from I-20 E. Continue on FM1382 S. Drive to W Belt Line Rd in Cedar Hill

COMPOUND INFORMATION	
Gate Combo	6789
Phone Company	Unkown
Power Company	Unkown
Meter # & Owner	Unkown



TOWER INFORMATION	
Tower Type	Guyed
Tower Manufacturer	Stainless, Inc.
Tower Tag Information	N/A
Structure Height	1455ft
Top of Highest Appurt. (AGL)	1529.3ft
Ground Elevation (AMSL)	830ft
FCC ID#	1055009
Notes / Additional Info	Was not able to access candelabra towers to get exact dimensions of upper TV antennas due to RF


ABBREVIATION DEFINITIONS							
ATC	American Tower Corp.	E.D.	Edge Distance	LLV	Long Leg Vertical	DNR	Did Not Record
AGL	Above Grade Level	M.E.	Minimum Edge	SLV	Short Leg Vertical	EW	Elliptical Waveguide
TOS	Top of Structure	THK	Thickness	BP	Bent Plate	FH	Foam Heliax
BOS	Bottom of Structure	OD	Outer Diameter	PL	Plate	MC	Metal Conduit
B/B	Bolt Center to Bolt Center	C	Channel	SR	Solid Round	RC	Rigid Conduit
C/C	Center to Center	HSS	Hollow Structural Sections	SCHL	Schifflerized Angle	SM	Smooth Heliax
I/I	Inside to Inside	L	Angle	S.B.	Stitch Bolts		
O/O	Outside to Outside	2L	Double Angle	CNR	Could Not Record		


Information Notes:


- Draw plan view of compound showing all physical features and/or dimensions.
- Show magnetic north and designate tower leg 'A' with magnetic azimuth.


COMPOUND PLAN SKETCH



GUYED & SST TOWER PROFILE with Antenna Details


GUYED & SST TOWER PROFILE with Antenna Details

GUYED & SST TOWER PROFILE with Antenna Details

GUYED & SST TOWER PROFILE with Antenna Details

Information Notes:


- Draw a front elevation view of climbing ladder(s) and waveguide ladder(s).
- Drawings can be typical when appropriate, showing typical dimensions.
- Climbing ladder width to be measured from inside to inside of ladder rails and step to be measured from center to center of rungs.
- Identify climbing ladders and waveguide ladders on coax plan view sketch.

LADDER AND WAVEGUIDES							
<u>Climbing Ladder Sketch</u>				<u>Waveguide Ladder Sketch</u>			
							
Description	No.	Height Btm to Top	Width	Step	Rail Material Type & Size	Rung Material Type & Size	Safety Wire Material Type & Size
Climbing	1	45' to 1455'	16-1/2"	12"	3/4" Solid Round	3/4" Solid Round	None
Description	No.	Height Btm to Top	Width	Step	Rail Material Type & Size	Rung Material Type & Size	Holes Qty, Size & Spacing
Waveguide							
Waveguide							

Information Notes:

- Draw a cross-section (elevation) drawing of each transmission line bridge(s).
- Drawings can be typical when appropriate, showing typical dimensions.

9




Information Notes:

- Draw a plan view of the tower showing all cables, conduits, coax, climbing ladders, waveguide ladders, etc.
- Identify **each** leg with a letter, starting at the northmost leg as 'A' and going clockwise. Correctly orient North arrow.
- Beginning with coax on "A" leg, number all coax clockwise.

10

TRANSMISSION CABLES INFORMATION




Coax No.	Type	Size	Height	Antenna No.	Carrier	Notes
1	Smooth	3/8"	107'	39	Rear Wall Shelter #1 Suite J	
2	Smooth	3/8"	262'	30	Rear Wall Shelter #1 Suite J	
3	Smooth	3/8"	262'	30	Rear Wall Shelter #1 Suite I	
4	Smooth	3/8"	262'	30	Rear Wall Shelter #1 Suite I	
5	Smooth	3/8"	262'	30	Rear Wall Shelter #1 Suite I	
6	TX	7/8"	405'	22	Rear Wall Shelter #1 Suite B	Enters in Suite B but may transfer to another Suite
7	TX	7/8"	170'	36	Rear Wall Shelter #1 Suite B	Enters in Suite B but may transfer to another Suite
8	TX	7/8"	326'	28	Rear Wall Shelter #1 Suite B	Enters in Suite B but may transfer to another Suite
9	TX	7/8"	65'	40	Rear Wall Shelter #1 Suite B	Enters in Suite B but may transfer to another Suite
10	Smooth	1/4"	DNR	N/A	N/A	Assumed to be dead along tower
11	TX	1 5/8"	1115'	-	Rear Wall Shelter	

Information Notes:

- Draw a plan view of the tower showing all cables, conduits, coax, climbing ladders, waveguide ladders, etc.
- Identify **each** leg with a letter, starting at the northmost leg as 'A' and going clockwise. Correctly orient North arrow.
- Beginning with coax on "A" leg, number all coax clockwise.

11

TRANSMISSION CABLES INFORMATION



Coax No.	Type	Size	Height	Antenna No.	Carrier	Notes
12	TX	1-5/8"	252'	31	Verizon	
13	TX	1-5/8"	252'	31	Verizon	
14	TX	4"	1095'	8	Rear Wall Shelter #1 Suite A	
15	TX	7/8"	528'	20	Rear Wall Shelter #1 Suite I	
16	TX	7/8"	577.5'	18 / 19	Rear Wall Shelter #1 Suite D	
17	TX	4"	840'	13	East Wall Shelter	
18	TX	1/2"	153'	37	Rear Wall Shelter #1 Suite D	
19	TX	7/8"	378'	24	Rear Wall Shelter #1 Suite D	
20	Cable	9/16"	1455'	N/A	ATC	Elevator Cable
21	Cable	9/16"	1455'	N/A	ATC	Elevator Cable
22	TX	1-1/4"	995'	9	Rear Wall Shelter #1 Suite M	


Information Notes:

- Draw a plan view of the tower showing all cables, conduits, coax, climbing ladders, waveguide ladders, etc.
- Identify **each** leg with a letter, starting at the northmost leg as 'A' and going clockwise. Correctly orient North arrow.
- Beginning with coax on "A" leg, number all coax clockwise.

12

TRANSMISSION CABLES INFORMATION

A (80°)




Information Notes:

- Draw a plan view of the tower showing all cables, conduits, coax, climbing ladders, waveguide ladders, etc.
- Identify **each** leg with a letter, starting at the northmost leg as 'A' and going clockwise. Correctly orient North arrow.
- Beginning with coax on "A" leg, number all coax clockwise.

13

TRANSMISSION CABLES INFORMATION




Coax No.	Type	Size	Height	Antenna No.	Carrier	Notes
35	MC	1-1/8"	1455'	N/A	ATC	Lighting
36	Smooth	1/4"	1455'	N/A	East Wall Shelter	Elevator Line
37	Rail	2"	1455'	N/A	ATC	Elevator Guides
38	Cable	5/8"	1455'	N/A	ATC	Elevator Cables
39	MC	1.66"	1443'	N/A	Rear Wall Shelter #1 Suite D	
40	Copper	8-3/16"	1465'	2	Rear Wall Shelter #1 Suite B	
41	Copper	5-1/4"	1303'	5	Rear Wall Shelter #1 Suite G	
42	TX	1-5/8"	252'	32	Verizon	
43	TX	1-5/8"	252'	32	Verizon	
44	TX	1-5/8"	252'	32	Verizon	
45	TX	1-5/8"	252'	32	Verizon	
46	Copper	6-1/4"	1380'	4	Rear Wall Shelter #1 Suite A	
47	Copper	3-1/8"	745'	15	N/A	Dead
48	Smooth	3/16"	131'	38	East Wall Shelter	
49	Smooth	3/16"	131'	38	East Wall Shelter	

Information Notes:

- Draw a plan view of the tower showing all cables, conduits, coax, climbing ladders, waveguide ladders, etc.
- Identify **each** leg with a letter, starting at the northmost leg as 'A' and going clockwise. Correctly orient North arrow.
- Beginning with coax on "A' leg, number all coax clockwise.

14





TRANSMISSION CABLES INFORMATION



Coax No.	Type	Size	Height	Antenna No.	Carrier	Notes
50	Smooth	3/16"	224'	33	East Wall Shelter	
51	Smooth	3/16"	224'	33	East Wall Shelter	
52	Smooth	3/16"	1455'	N/A	Rear Wall Shelter #1 Suite I	Unused
53	TX	2-1/2"	1380'	4,5	Rear Wall Shelter #1 Suite I	
54	TX	5/8"	362'	25	Rear Wall Shelter #1 Suite J	
55	Smooth Bundle	(8) 5/8"	658'	16	Pad at Base of Tower	
56	Smooth Bundle	(8) 5/8"	658'	16	Pad at Base of Tower	
57	Smooth Bundle	(8) 5/8"	658'	16	Pad at Base of Tower	
58	Copper	8-1/4"	1485'	3	Rear Wall Shelter #1 Suite J	
59	Copper	7-1/4"	1465'	1	Rear Wall Shelter #1 Suite G	

Information Notes:






- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.

ANTENNA AND MOUNT INFORMATION									
Front or Side Elevation			Plan View		Photo of Antenna				
									
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier		
1	1443' Mount Base	CA	Tower off Candelabra	20	7-1/4" Copper	59	Rear Wall Shelter #1 Suite G		
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.				
Unk	Unk		CNR, Approximate: 8" x 60'						
Front or Side Elevation			Plan View		Photo of Antenna				
									
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier		
2	1443' Mount Base	AB	Tower off Candelabra	140	8-3/16" Copper	40	Rear Wall Shelter #1 Suite B		
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.				
Unk	Unk		CNR, Approximate: 15" x 80'						

Information Notes:

- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.

16

ANTENNA AND MOUNT INFORMATION									
Front or Side Elevation			Plan View			Photo of Antenna			
									
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier		
3	1443' Mount Base	BC	Tower off Candelabra	260	8-1/4" Copper	58	Rear Wall Shelter #1 Suite J		
Ant. Manufacturer	Antenna Model #			Antenna Dimensions		TMA Qty/ Model or Dim.			
Unk	Unk			CNR, Approximate: 15" x 60'					
Front or Side Elevation			Plan View			Photo of Antenna			
									
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier		
4	1380' Center	All (3) Faces	Each bay has a 2' x 2' x 13' Wide frame	20 / 140 / 260	6-1/4" Copper, 2-1/2" TX	46, 53	Rear Wall Shelter #1 Suite A		
Ant. Manufacturer	Antenna Model #			Antenna Dimensions		TMA Qty/ Model or Dim.			
Unk	Unk			(8) Bay FM with 6" Dia.x 24" Elements @ Approx. 10' Spacing					

Information Notes:

- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.

17

ANTENNA AND MOUNT INFORMATION							
Front or Side Elevation			Plan View		Photo of Antenna		
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
5	1303' Center	All (3) Faces	Each bay has a 2' x 2' x 13' Wide frame	20 / 140 / 260	(1) 5-1/4" Copper (1) 2-1/2" TX	41, 53	Rear Wall Shelter #1 Suite G
Ant. Manufacturer	Antenna Model #			Antenna Dimensions		TMA Qty/ Model or Dim.	
Unk	Unk			(6) Bay FM with 6" Dia.x 24" Elements @ Approx. 10' Spacing			

Front or Side Elevation			Plan View			Photo of Antenna	
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
6	1156' Center	A	(2) Sidearms	60	4" Copper	33	East Wall Shelter
Ant. Manufacturer	Antenna Model #			Antenna Dimensions		TMA Qty/ Model or Dim.	

Information Notes:

- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.

18

ANTENNA AND MOUNT INFORMATION							
Front or Side Elevation			Plan View			Photo of Antenna	
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
7	1132.5' & 1145' Center	C	2.375" X 30' Pipe	50	1-5/8"	11	Rear Wall Shelter #1 Suite I
Ant. Manufacturer		Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.	
KATHREIN		CL-46/HRM/50N		6' (6) Element			

Front or Side Elevation			Plan View			Photo of Antenna	
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
8	1095' Center	C	Triangular Sidearm	30 / 230	4"	14	Rear Wall Shelter #1 Suite A
Ant. Manufacturer		Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.	
Rymsa		AT-1S-250/5132		(8) Sets of (2) Panels, 38-1/2"			

Information Notes:

- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.

19

ANTENNA AND MOUNT INFORMATION							
Front or Side Elevation			Plan View		Photo of Antenna		
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
9	995' Center	B	Sidearm	170	(1) 1-1/4" TX (1) 7/8" OD	22, 23	Rear Wall Shelter #1 Suite M
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.		
Superquad	Unk		36" Dia. x 41"				

Front or Side Elevation			Plan View		Photo of Antenna		
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
10	895.5' Base	CA	Platform	20	1-7/8" / 2-3/8"	25, 27	Rear Wall Shelter #1 Suite M
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.		
Telewave, Inc.	ANT150F6-L		2" x 20'		See #12		

Information Notes:

- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.





20

ANTENNA AND MOUNT INFORMATION							
Front or Side Elevation			Plan View		Photo of Antenna		
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
11	892.5' Base	CA	Platform	40	1-7/8" / 2-3/8"	25, 27	Rear Wall Shelter #1 Suite M
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.		
Unk	Unk		(16) Element x 16' Inverted Dipole		See #12		

Front or Side Elevation			Plan View		Photo of Antenna		
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
12	896.5' Base	A	On 4' x 2' x 2' Cabinet	80	1-7/8" / 2-3/8"	25, 27	Rear Wall Shelter #1 Suite M
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.		
Unk	Unk		3" GPS		Additional Cabinets 24" x 15" x 22" Face AB on platform 34" x 12" x 4" Face AB on tower (2) 17" x 12" x 5" Face CA on tower 48" x 24" x 24" Face CA on platform		

Information Notes:



- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.



ANTENNA AND MOUNT INFORMATION									
Front or Side Elevation			Plan View		Photo of Antenna				
									
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier		
13	840' Center	C	Triangular Sidearm	30 / 230	4"	17	East Wall Shelter		
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.				
Unk	Unk		(8) Sets of (2) Panels, 38-1/2" x 14" x 7" Each						
Front or Side Elevation			Plan View		Photo of Antenna				
									
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier		
14	793' Center	C	Triangular Sidearm	30 / 230	3"	26	Rear Wall Shelter #1 Suite A		
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.				
Unk	Unk		(4) Sets of (2) Panels, 38-1/2" x 14" x 7" Each						

Information Notes:

- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.

22

ANTENNA AND MOUNT INFORMATION							
Front or Side Elevation			Plan View			Photo of Antenna	
							
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
15	745' Center	C	3" x 32' Pipe	10	3-1/8"	47	Dead
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.		
Unk	Unk		(8) Bay FM, 10' Spacing, Approx. 24" x 30" Bays				

Front or Side Elevation			Plan View			Photo of Antenna	
							
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
16	658' Center	A/B/C	Small Face Frame	20 / 120 / 320	(24) 5/8"	55/56 /57	Pad at Base of Tower
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.		
Alvarion	AN1453-01 REV A		Approx. 4' x 10" x 3"		(4) Alvarion BMAX-B5T-AU-ODU Each (4) RET Each		

Information Notes:

- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.





23

ANTENNA AND MOUNT INFORMATION							
Front or Side Elevation			Plan View		Photo of Antenna		
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
17	591' Center	CA	Triangular Sidearm	30 / 230	3"	31	Rear Wall Shelter #1 Suite B
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.		
Unk	Unk		(8) Sets of (2) Panels, 38-1/2" x 14" x 7" Each				

Front or Side Elevation			Plan View		Photo of Antenna		
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
18	577.5' Center	A	Shared with No. 19	350	7/8" TX	16	Rear Wall Shelter #1 Suite D
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.		
Unk	Unk		4' x (5) Element Yagi				





Information Notes:

- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.

ANTENNA AND MOUNT INFORMATION									
Front or Side Elevation			Plan View		Photo of Antenna				
									
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier		
19	569.5' Center	CA	1-1/2" Sidearm at top and bottom	50	7/8" TX	16	Rear Wall Shelter #1 Suite D		
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.				
Unk	Unk		(8) Element x 16' Dipole		(1) 12" x 3" x 3"				
Front or Side Elevation			Plan View		Photo of Antenna				
									
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier		
20	528' Center	A	2-7/8" x 4' Pipe with 2-3/8" Tieback	20	7/8" TX	15	Rear Wall Shelter #1 Suite I		
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.				
Unk	Unk		10' Grid Dish						





Information Notes:

- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.

ANTENNA AND MOUNT INFORMATION									
Front or Side Elevation			Plan View			Photo of Antenna			
									
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier		
21	410' Center	C	Direct to Leg	0	N/A	N/A	N/A		
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.				
N/A	N/A		Unused 10' x 7' Ice Shield for #24						
Front or Side Elevation			Plan View			Photo of Antenna			
									
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier		
22	405' Center	A	Direct to Leg	20	7/8" TX	6	Rear Wall Shelter #1 Suite B		
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.				
Unk	Unk		30" x (6) Element Yagi						





Information Notes:

- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.

ANTENNA AND MOUNT INFORMATION									
Front or Side Elevation		Plan View			Photo of Antenna				
									
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier		
23	387' Center	A	Direct to Leg	40	N/A	N/A	N/A		
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.				
N/A	N/A		Unused 6' x 5' Ice Shield for #26						
Front or Side Elevation		Plan View			Photo of Antenna				
									
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier		
24	378' Center	C	2.875" x 4' Pipe	20	7/8" TX	19	Rear Wall Shelter #1 Suite D		
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.				
Unk	Unk		8' Grid Dish						

Information Notes:

- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.

ANTENNA AND MOUNT INFORMATION									
Front or Side Elevation			Plan View		Photo of Antenna				
									
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier		
25	362' Center	A	4" x 4' Pipe	80	5/8" Smooth	54	Rear Wall Shelter #1 Suite J		
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.				
Unk	Unk		4' Dish						
Front or Side Elevation			Plan View		Photo of Antenna				
									
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier		
26	352.5' Center	A	4" x 4' Pipe w/(2) 2.375" Tiebacks	30	EW 63	24	Rear Wall Shelter #1 Suite B		
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.				
Andrew	UHX8		8 Dish/Drum						

Information Notes:

- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.

28

ANTENNA AND MOUNT INFORMATION							
Front or Side Elevation			Plan View			Photo of Antenna	
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
27	333' Center	C	4.5" x 4' Pipe with 12" Sidearm and 1.9" Tieback	20	1-5/8" TX	28	Rear Wall Shelter #1 Suite B
Ant. Manufacturer		Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.	
Unk		Unk		10' Grid Dish			

Front or Side Elevation			Plan View			Photo of Antenna	
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
28	326' Center	A	4.5" x 4' Pipe with 12" Sidearm and 1.9" Tieback	20	7/8" TX	8	Rear Wall Shelter #1 Suite B
Ant. Manufacturer		Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.	
Unk		Unk		10' Grid Dish			

Information Notes:

- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.

29

ANTENNA AND MOUNT INFORMATION							
Front or Side Elevation			Plan View			Photo of Antenna	
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
29	306 Center	CA	Direct to Tower	20	N/A	N/A	N/A
Ant. Manufacturer	Antenna Model #			Antenna Dimensions		TMA Qty/ Model or Dim.	
N/A	N/A			10' x 4' 2" Ice Shield			

Front or Side Elevation			Plan View			Photo of Antenna	
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
30	262' Center	B / C	4.5" x 5' Pipe with 20" Sidearm and 1.9" Tieback	110 / 210	3/8" Smooth	2-5	Rear Wall Shelter #1 Suite I
Ant. Manufacturer	Antenna Model #			Antenna Dimensions		TMA Qty/ Model or Dim.	
Unk	SBX2-107CNEC			(2) 3' Dishes with 6' x 4' Ice Shields at 267'		(1) Small ODU each	

Information Notes:

- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.

ANTENNA AND MOUNT INFORMATION							
Front or Side Elevation			Plan View		Photo of Antenna		
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
31	252' Center	A	10' 6" x 3' Sector Frame	20	(2) 1-5/8" TX	12/13	Verizon
Ant. Manufacturer		Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.	
(1) CSS (1) Jaybeam		(1) X7C-665-6-I-B (1) PCSX065-18-2		See Make/Model		(1) Total - Powerwave LGP 18601	

Front or Side Elevation			Plan View		Photo of Antenna		
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
32	252' Center	B / C	13' x 3' Sector Frame	140 / 260	(4) 1-5/8" TX	42-45	Verizon
Ant. Manufacturer		Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.	
(2) CSS (2) Jaybeam		(2) X7C-665-6-I-B (2) PCSX065-18-2		See Make/Model		(2) Total - Powerwave LGP 18601	

Information Notes:

- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.

ANTENNA AND MOUNT INFORMATION								
Front or Side Elevation			Plan View			Photo of Antenna		
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier	
33	224' Center	CA	1.5" x 4' Horizontal Pipe	20	3/16" Smooth	50/51	East Wall Shelter	
Ant. Manufacturer		Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.		
Unk		Unk		3' Dish		(1) 12" x 8" x 4"		

Front or Side Elevation			Plan View			Photo of Antenna		
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier	
34	203' Center	C	4.5" x 6' Pipe with 1.9" Tieback	20	7/8" TX	29	Rear Wall Shelter #1 Suite K	
Ant. Manufacturer		Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.		
Unk		Unk		8' Grid Dish with 12' x 9' Ice Shield at 212.5'				

Information Notes:

- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.

ANTENNA AND MOUNT INFORMATION							
Front or Side Elevation			Plan View			Photo of Antenna	
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
35	187.5' Center	C	4.5" x 4' Pipe	20	7/8" TX	30	Rear Wall Shelter #1 Suite K
Ant. Manufacturer	Antenna Model #		Antenna Dimensions			TMA Qty/ Model or Dim.	
Unk	Unk		8' Grid Dish				

Front or Side Elevation			Plan View			Photo of Antenna	
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
36	170' Center	C	2.375" x 4' Pipe	30	7/8" TX	7	Rear Wall Shelter #1 Suite B
Ant. Manufacturer	Antenna Model #		Antenna Dimensions			TMA Qty/ Model or Dim.	
Unk	Unk		10' Grid Dish				

Information Notes:

- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.

33

ANTENNA AND MOUNT INFORMATION							
Front or Side Elevation			Plan View			Photo of Antenna	
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
37	153' Center	C	Direct to Leg	320	1/2" TX	18	Rear Wall Shelter #1 Suite D
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.		
Unk	Unk		(6) Element x 18" Yagi				

Front or Side Elevation			Plan View			Photo of Antenna	
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
38	131' Center	CA	1.9" x 8' Pipe	20	3/16" Smooth	48/49	East Wall Shelter
Ant. Manufacturer	Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.		
Unk	Unk		3' Dish		(2) 4" x 4" TMAs		

Information Notes:

- Draw an elevation and plan view of each antenna showing all dimensions of mount and antenna. Insert photo of antenna and mount.
- Indicate the location of the elevation given in the table with a marker on the elevation view.
- Drawings can be used to show single antennas, sectors or platforms.

34

ANTENNA AND MOUNT INFORMATION							
Front or Side Elevation			Plan View		Photo of Antenna		
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
39	107' Center	A	2' x 2' Sidearm	20	3/8" Smooth	1	Rear Wall Shelter #1 Suite J
Ant. Manufacturer		Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.	
Unk		Unk		(5) Element x 18" Yagi			

Front or Side Elevation			Plan View		Photo of Antenna		
No.	Elevation	Leg	Mount Type	Azimuth	Coax Size	Coax #	Carrier
40	65' Base	A	3' x 2'-6" Sidearm	80	7/8" TX	9	Rear Wall Shelter #1 Suite B
Ant. Manufacturer		Antenna Model #		Antenna Dimensions		TMA Qty/ Model or Dim.	
Unk		Unk		2" x 10' Omni			

Information Notes:

- Photo Ranges are acceptable.
- Note elevations or specific anchors for a range or photo when relevant.
- Number file names of photos with 001, 002, 003, etc. so photos will display in order.